

TCR ADVANCED 1 KOM

GIANT



SPECS

| FRAME | |
|-------------------------|--|
| SIZES | XS, S, M, M/L, L, XL |
| COLORS | Asphalt Green, Mars Dust |
| FRAME | Advanced-Grade Composite, 12x142mm thru-axle, disc |
| FORK | Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc |
| COMPONENTS | |
| HANDLEBAR | Giant Contact XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm |
| GRIPS | Stratus Lite 2.0 |
| STEM | Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm |
| SEATPOST | Giant Variant, composite, -5/+15mm offset |
| SADDLE | Giant Approach |
| PEDALS | N/A |
| DRIVETRAIN | |
| SHIFTERS | Shimano 105 Di2 |
| FRONT DERAILLEUR | Shimano 105 Di2 FD-R8150 |
| REAR DERAILLEUR | Shimano 105 Di2 RD-R8150 |
| BRAKES | Shimano 105 Di2 hydraulic, Giant MPH rotors [F]160mm, [R]140mm |
| BRAKE LEVERS | Shimano 105 Di2 |
| CASSETTE | Shimano 105, 12-speed, 11x36 |
| CHAIN | KMC X12L-1 |
| CRANKSET | Shimano 105, 34/50 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm |
| BOTTOM BRACKET | Shimano, press fit |

| WHEELS | |
|---------------------------|---|
| RIMS | Giant P-R2, [F]36mm, [R]36mm |
| HUBS | 12mm thru-axle |
| SPOKES | stainless |
| TIRES | Giant Gavia Course 1, tubeless, 700x25c (28mm), folding |
| EXTRAS | tubeless prepared, 33mm max tire size |
| LIMITS | |
| MAX TIRE CLEARANCE | 33mm |

GEOMETRY

| FRAME | XS | S | M | ML | L | XL |
|--------------------------|-------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 425 | 445 | 470 | 500 | 530 | 560 |
| Seat Tube Angle | 74.5° | 74.0° | 73.5° | 73.0° | 73.0° | 72.5° |
| Top Tube Length (mm) | 520 | 535 | 550 | 565 | 580 | 600 |
| Head Tube Length (mm) | 120 | 130 | 145 | 165 | 185 | 200 |
| Head Tube Angle | 71.0° | 72.3° | 73.5° | 73.0° | 73.0° | 72.5° |
| Fork Rake (mm) | 45 | 45 | 45 | 45 | 45 | 45 |
| Trail (mm) | 72 | 64 | 59 | 59 | 59 | 59 |
| Wheelbase (mm) | 976 | 977 | 980 | 991 | 1006 | 1020 |
| Chain Stay Length (mm) | 405 | 405 | 405 | 405 | 405 | 405 |
| Bottom Bracket Drop (mm) | 72 | 69.5 | 69.5 | 67 | 67 | 67 |
| Stack (mm) | 517 | 528 | 545 | 562 | 581 | 596 |
| Reach (mm) | 376 | 383 | 388 | 393 | 402 | 412 |
| Stand Over Height (mm) | 703 | 722 | 743 | 771 | 798 | 822 |
| Handlebar Width (mm) | 400 | 400 | 420 | 420 | 440 | 440 |
| Stem Length (mm) | 80 | 90 | 100 | 110 | 110 | 120 |
| Crank Length (mm) | 170 | 170 | 172.5 | 172.5 | 175 | 175 |
| Wheel Size | 700C | 700C | 700C | 700C | 700C | 700C |

All specifications listed are subject to change without notice.