

TCR ADVANCED 1 - PRO COMPACT



ESPECIFICACIONES

CUADRO	
CUADRO	Advanced-Grade Composite, 12x142mm thru-axle, Disc
HORQUILLA	Advanced-Grade Composite, Full-Composite OverDrive Steerer, 12x100mm thru-axle, Disc
COMPONENTES	
MANILLAR	Giant Contact
PUÑOS	Stratus Lite 2.0 w/ gel
POTENCIA	Giant Contact Aerolight, -10 degree
TIJA DE SILLÍN	Giant Variant, Composite Offset -5/+15mm
SILLÍN	Giant Approach 7mm Steel Rail, with UniClip / ParticleFlow technology
PEDALES	GCS,GT5:Platform Pedal Rest GSC : no pedal
TUBO DE DIRECCIÓN	HS-GTOD1-01
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano 105 Di2 HRD
DESVIADOR	Shimano 105 Di2
CAMBIO TRASERO	Shimano 105 Di2
FRENOS	Shimano 105 Di2 HRD
PALANCAS DE FRENOS	Shimano 105 Di2 HRD
CASETTE	Shimano 105 Di2, 11x34, 12-speed
CADENA	KMC X12L-1
JGO. PLATOS Y BIELAS	Shimano 105 Di2, FC-R7100, 36/52
CAJA DE PEDALIER	Shimano, PressFit 71

RUEDAS	
LLANTAS	Giant P-R1 Disc 12mm Thru-Axle
BUJES	Giant P-R1 Disc 12mm Thru-Axle
RADIOS	Giant P-R1 Disc 12mm Thru-Axle
CUBIERTAS	Giant Gavia COURSE 0 Tubeless, 700x30C, 170 TPI, Folding
EXTRAS	Tubeless Prepared
LÍMITES	
MÁXIMA ANCHURA DE NEUMÁTICO	700x33mm

Precio: 3.299,00 €

GEOMETRÍA

CUADRO	XS	S	M	ML	L	XL
Ángulo del tubo del sillín	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Longitud del tubo superior (mm) (mm)	520	535	550	565	580	600
Longitud del tubo de dirección (mm) (mm)	120	130	145	165	185	200
Ángulo del tubo de dirección	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Distancia entre ejes (mm) (mm)	976	977	980	991	1006	1020
Longitud de la vaina (mm) (mm)	405	405	405	405	405	405
Stack (mm) (mm)	517	528	545	562	581	596
Reach (mm) (mm)	376	383	388	393	402	412
Altura del suelo al tubo (mm) (mm)	719	734	752	768	786	803
Longitud de las bielas (mm) (mm)	165	165	170	170	172,5	172,5

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.