

TCR ADVANCED 1 (PRO COMPACT)

GIANT

SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Purple Haze/Ultra Violet, Dreamy Blue
OKVIR	Advanced-grade Composite, 12x142mm thru-axle, disc
VILICE	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Contact XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm
GRIPS	Stratus Lite 2.0
OPORA KRMILA	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
OPORA SEDEŽA	Giant Variant, composite, -5/+15mm offset
SEDEŽ	Giant Approach
POGON	
PRESTAVNE ROČICE	Shimano 105 Di2
PREDNJI MENJALNIK	Shimano 105 Di2 FD-7150
ZADNJI MENJALNIK	Shimano 105 Di2 RD-7150
ZAVORE	Shimano 105 Di2 hydraulic, Shimano SM-RT64 rotors [F]160mm, [R]140mm
ZAVORNE ROČICE	Shimano 105 Di2
VERIŽNIK	Shimano 105, 12-speed, 11x34
VERIGA	KMC X12L-1
GONILKE Z VERIŽNIKI	Shimano 105, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant P-R1 Disc wheelset, alloy, [F]30mm, [R]30mm
PESTA	Giant alloy, 12mm thru-axle
NAPERE	stainless
PLAŠČI	Giant Gavia Course 0, tubeless, 700x28c (28mm), folding
DODATKI	tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	425	445	470	500	530	560
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Višina glave okvirja (mm)	120	130	145	165	185	200
Krmilni kot	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Zamik vpetja osi (mm)	45	45	45	45	45	45
Trail (mm)	72,1	64	59,2	59,2	59,2	59,2
Medosna razdalja (mm)	976	977	980	991	1006	1020
Dolžina cevi ob verigi (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Oddaljenost zgornje cevi od gonilne osi (mm)	517	528	545	562	581	596
Doseg (mm)	376	383	388	393	402	412
Višina zgornje cevi (mm)	719	734	752	768	786	803
Širina krmila (mm)	380	380	400	400	420	420
Dolžina opore krmila (mm)	80	90	100	110	110	120
Dolžina gonilke (mm)	165	165	170	170	172,5	172,5

Ve navedene specifikacije se lahko spremenijo brez obvestila.