



SPECIFIKACIJE

| OKVIR               |                                                                                      |
|---------------------|--------------------------------------------------------------------------------------|
| VELIKOSTI           | XS, S, M, M/L, L, XL                                                                 |
| BARVE               | Carbon, Illusion White                                                               |
| OKVIR               | Advanced-Grade Composite, 12x142mm thru-axle, disc                                   |
| VILICE              | Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc |
| KOMPONENTE          |                                                                                      |
| KRMILO              | Giant Contact XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm                     |
| GRIPS               | Stratus Lite 2.0                                                                     |
| OPORA KRMILA        | Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm       |
| OPORA SEDEŽA        | Giant Variant, composite, -5/+15mm offset                                            |
| SEDEŽ               | Giant Approach                                                                       |
| PEDALA              | N/A                                                                                  |
| POGON               |                                                                                      |
| PRESTAVNE ROČICE    | Shimano 105                                                                          |
| PREDNJI MENJALNIK   | Shimano 105                                                                          |
| ZADNJI MENJALNIK    | Shimano 105                                                                          |
| ZAVORE              | Shimano 105 hydraulic, Giant MPH rotors [F]160mm, [R]140mm                           |
| ZAVORNE ROČICE      | Shimano 105                                                                          |
| VERIŽNIK            | Shimano 105, 12-speed, 11x36                                                         |
| VERIGA              | KMC X12L-1                                                                           |
| GONILKE Z VERIŽNIKI | Shimano 105, 34/50 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm      |
| BOTTOM BRACKET      | Shimano, press fit                                                                   |

| OBROČNIKI          |                                                         |
|--------------------|---------------------------------------------------------|
| OBROČI             | Giant P-R2, [F]36mm, [R]36mm                            |
| PESTA              | 12mm thru-axle                                          |
| NAPERE             | stainless                                               |
| PLAŠČI             | Giant Gavia Course 1, tubeless, 700x25c (28mm), folding |
| DODATKI            | tubeless prepared, 33mm max tire size                   |
| LIMITS             |                                                         |
| MAX TIRE CLEARANCE | 33mm                                                    |

GEOMETRIJA

| OKVIR                                        | XS    | S     | M     | ML    | L     | XL    |
|----------------------------------------------|-------|-------|-------|-------|-------|-------|
| Dolžina sedežne cevi (mm)                    | 425   | 445   | 470   | 500   | 530   | 560   |
| Kot sedežne cevi                             | 74,5° | 74,0° | 73,5° | 73,0° | 73,0° | 72,5° |
| Top Tube Length (mm)                         | 520   | 535   | 550   | 565   | 580   | 600   |
| Višina glave okvirja (mm)                    | 120   | 130   | 145   | 165   | 185   | 200   |
| Krmilni kot                                  | 71,0° | 72,3° | 73,5° | 73,0° | 73,0° | 72,5° |
| Zamik vpetja osi (mm)                        | 45    | 45    | 45    | 45    | 45    | 45    |
| Trail (mm)                                   | 72    | 64    | 59    | 59    | 59    | 59    |
| Medosna razdalja (mm)                        | 976   | 977   | 980   | 991   | 1006  | 1020  |
| Dolžina cevi ob verigi (mm)                  | 405   | 405   | 405   | 405   | 405   | 405   |
| Bottom Bracket Drop (mm)                     | 72    | 69,5  | 69,5  | 67    | 67    | 67    |
| Oddaljenost zgornje cevi od gonilne osi (mm) | 517   | 528   | 545   | 562   | 581   | 596   |
| Doseg (mm)                                   | 376   | 383   | 388   | 393   | 402   | 412   |
| Višina zgornje cevi (mm)                     | 703   | 722   | 743   | 771   | 798   | 822   |
| Širina krmila (mm)                           | 400   | 400   | 420   | 420   | 440   | 440   |
| Dolžina opore krmila (mm)                    | 80    | 90    | 100   | 110   | 110   | 120   |
| Dolžina gonilke (mm)                         | 170   | 170   | 172,5 | 172,5 | 175   | 175   |
| Velikost obročnikov                          | 700C  | 700C  | 700C  | 700C  | 700C  | 700C  |

Vse navedene specifikacije se lahko spremenijo brez obvestila.