

# TCR ADVANCED 2-PC



## ESPECIFICACIONES

| CUADRO               |                                                                                      |
|----------------------|--------------------------------------------------------------------------------------|
| TALLAS               | XS, S, M, M/L, L, XL                                                                 |
| COLORES              | Polar Night/Unicorn White, Pearl White/Cyber Sunset                                  |
| CUADRO               | Advanced-grade composite, 12x142mm thru-axle, disc                                   |
| HORQUILLA            | Advanced-grade composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc |
| COMPONENTES          |                                                                                      |
| MANILLAR             | Giant Contact XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm                     |
| PUÑOS                | Stratus Lite 2.0                                                                     |
| POTENCIA             | Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm       |
| TIJA DE SILLÍN       | Giant Variant, composite, -5/+15mm offset                                            |
| SILLÍN               | Giant Approach                                                                       |
| TRANSMISIÓN          |                                                                                      |
| MANETAS DE CAMBIO    | Shimano 105                                                                          |
| DESVIADOR            | Shimano 105                                                                          |
| CAMBIO TRASERO       | Shimano 105                                                                          |
| FRENOS               | Shimano 105 hydraulic, Shimano SM-RT64 rotors [F]160mm, [R]140mm                     |
| PALANCAS DE FRENOS   | Shimano 105 Di2                                                                      |
| CASETTE              | Shimano 105, 12-speed, 11x34                                                         |
| CADENA               | KMC X12L-1                                                                           |
| JGO. PLATOS Y BIELAS | Shimano 105, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm      |
| CAJA DE PEDALIER     | Shimano, press fit                                                                   |

| RUEDAS                      |                                                   |
|-----------------------------|---------------------------------------------------|
| LLANTAS                     | Giant P-R1 Disc wheelset, alloy, [F]25mm, [R]25mm |
| BUJES                       | Giant alloy, 12mm thru-axle                       |
| RADIOS                      | stainless                                         |
| CUBIERTAS                   | Giant Gavia Course 0, tubeless, 700x30c, folding  |
| EXTRAS                      | Tubeless Prepared                                 |
| LÍMITES                     |                                                   |
| MÁXIMA ANCHURA DE NEUMÁTICO | 33mm                                              |

Precio: 2.599,00 €

## GEOMETRÍA

| CUADRO                                   | XS    | S     | M     | ML    | L     | XL    |
|------------------------------------------|-------|-------|-------|-------|-------|-------|
| Longitud del tubo del sillín (mm)        | 425   | 445   | 470   | 500   | 530   | 560   |
| Ángulo del tubo del sillín               | 74,5° | 74,0° | 73,5° | 73,0° | 73,0° | 72,5° |
| Longitud del tubo superior (mm) (mm)     | 520   | 535   | 550   | 565   | 580   | 600   |
| Longitud del tubo de dirección (mm) (mm) | 120   | 130   | 145   | 165   | 185   | 200   |
| Ángulo del tubo de dirección             | 71,0° | 72,3° | 73,0° | 73,0° | 73,0° | 73,0° |
| Inclinación de la horquilla (mm)         | 45    | 45    | 45    | 45    | 45    | 45    |
| Trail (mm) (mm)                          | 72,1  | 64    | 59,2  | 59,2  | 59,2  | 59,2  |
| Distancia entre ejes (mm) (mm)           | 976   | 977   | 980   | 991   | 1006  | 1020  |
| Longitud de la vaina (mm) (mm)           | 405   | 405   | 405   | 405   | 405   | 405   |
| Caída del eje de pedalier (mm) (mm)      | 72    | 70    | 70    | 67    | 67    | 67    |
| Stack (mm) (mm)                          | 517   | 528   | 545   | 562   | 581   | 596   |
| Reach (mm) (mm)                          | 376   | 383   | 388   | 393   | 402   | 412   |
| Altura del suelo al tubo (mm) (mm)       | 719   | 734   | 752   | 768   | 786   | 803   |
| Ancho del manillar (mm) (mm)             | 380   | 380   | 400   | 400   | 420   | 420   |
| Longitud de la potencia (mm) (mm)        | 80    | 90    | 100   | 110   | 110   | 120   |
| Longitud de las bielas (mm) (mm)         | 165   | 165   | 170   | 170   | 172,5 | 172,5 |

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.