

# TCR ADVANCED 2 PC

**GIANT**

## TEKNISET TIEDOT

| RUNKO          |  |
|----------------|--|
| KOOT           | XS, S, M, M/L, L, XL   |
| VÄRIT          | Carbon, Illusion White   |
| RUNKO          | Advanced-Grade Composite, 12x142mm thru-axle, disc                                   |
| HAARUKKA       | Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc |
| KOMPONENTIT    |  |
| OHJAUSTANKO    | Giant Contact XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm                     |
| GRIPIT         | Stratus Lite 2.0   |
| OHJAINKANNATIN | Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm       |
| SATULATOLPPA   | Giant Variant, composite, -5/+15mm offset  |
| SATULA         | Giant Approach   |
| POLKIMET       | N/A  |
| VOIMANSIIRTO   |  |
| VAIHDEVIPU     | Shimano 105  |
| ETUVAIHTAJA    | Shimano 105  |
| TAKAVAIHTAJA   | Shimano 105  |
| JARRUT         | Shimano 105 hydraulic, Giant MPH rotors [F]160mm, [R]140mm                           |
| JARRUKAHVAT    | Shimano 105  |
| RATASPAKKA     | Shimano 105, 12-speed, 11x34   |
| KETJUT         | KMC X12L-1   |
| KAMPISARJA     | Shimano 105, 36/52 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm      |
| KESKIÖ         | Shimano, press fit   |

| RENKAAT        |   |
|----------------|---|
| VANTEET        | Giant P-R2, [F]25mm, [R]25mm                            |
| NAVAT          | 12mm thru-axle  |
| PINNAT         | stainless   |
| RENKAAT        | Giant Gavia Course 1, tubeless, 700x25c (28mm), folding |
| LISÄTIEDOT     | tubeless prepared, 33mm max tire size                   |
| RAJOITTEET     |   |
| MAX RENGASVARA | 33mm  |

Suositus hinta: 2 899,00 €

## GEOMETRIA

| RUNKO                              | S     | M     | ML    | L     | XL    |
|------------------------------------|-------|-------|-------|-------|-------|
| Satulaputken pituus (mm)           | 445   | 470   | 500   | 530   | 560   |
| Satulaputken kulma                 | 74,0° | 73,5° | 73,0° | 73,0° | 72,5° |
| Vaakaputken pituus (mm)            | 535   | 550   | 565   | 580   | 600   |
| Emäputken pituus (mm)              | 130   | 145   | 165   | 185   | 200   |
| Emäputken kulma                    | 72,3° | 73,5° | 73,0° | 73,0° | 72,5° |
| Haarukan offset (mm)               | 45    | 45    | 45    | 45    | 45    |
| Trail-mitta (mm)                   | 64    | 59    | 59    | 59    | 59    |
| Akseliväli (mm)                    | 977   | 980   | 991   | 1006  | 1020  |
| Takahaarukan alaputken pituus (mm) | 405   | 405   | 405   | 405   | 405   |
| Keskiön pudotus (mm)               | 69,5  | 69,5  | 67    | 67    | 67    |
| Stack-mitta (mm)                   | 528   | 545   | 562   | 581   | 596   |
| Reach-mitta (mm)                   | 383   | 388   | 393   | 402   | 412   |
| Standover-mitta (mm)               | 722   | 743   | 771   | 798   | 822   |
| Ohjaustangon leveys (mm)           | 400   | 420   | 420   | 440   | 440   |
| Ohjainkannattimen pituus (mm)      | 90    | 100   | 110   | 110   | 120   |
| Kammen pituus (mm)                 | 170   | 172,5 | 172,5 | 175   | 175   |
| Rengaskoko                         | 700C  | 700C  | 700C  | 700C  | 700C  |

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.