



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Gloss Misty Forest/Matte Gunmetal Black
OKVIR	Advanced-Grade Composite, disc
VILICE	Advanced-Grade Composite, full-composite OverDrive steerer, disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Contact XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Stratus Lite 3.0
OPORA KRMILA	Giant Contact XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
OPORA SEDEŽA	Giant Variant, composite, -5/+15mm offset
SEDEŽ	Giant Approach
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM Rival eTap AXS
PREDNJI MENJALNIK	SRAM Rival eTap AXS
ZADNJI MENJALNIK	SRAM Rival eTap AXS
ZAVORE	SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	SRAM Rival eTap AXS hydraulic
VERIŽNIK	SRAM Rival, 12-speed, 10x36
VERIGA	SRAM Rival D1
GONILKE Z VERIŽNIKI	SRAM Rival D1 DUB, 33/46 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant SLR 2 36 Carbon Disc WheelSystem, [F] 36mm, [R] 36mm
PESTA	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant alloy, 3-pawl driver, CenterLock, 12mm thru-axle
NAPERE	Sapim Sprint
PLAŠČI	Giant Fondo 1, tubeless, 700x28c (32mm), folding
DODATKI	tubeless prepared, 32mm max tire size

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	425	445	470	500	530	560
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Višina glave okvirja (mm)	120	130	145	165	185	200
Krmilni kot	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Zamik vpetja osi (mm)	45	45	45	45	45	45
Trail (mm)	72,1	64	59,2	59,2	59,2	59,2
Medosna razdalja (mm)	976	977	980	991	1006	1020
Dolžina cevi ob verigi (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Oddaljenost zgornje cevi od gonilne osi (mm)	517	528	545	562	581	596
Doseg (mm)	376	383	388	393	402	412
Višina zgornje cevi (mm)	706	725	747	773	800	816
Širina krmila (mm)	400	400	420	420	440	440
Dolžina opore krmila (mm)	80	90	100	110	110	120
Dolžina gonilke (mm)	170	170	172,5	172,5	175	175
Velikost obročnikov	700C	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.