

TCR ADVANCED PRO 0 AXS

GIANT



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Ocean Twilight / Glare Chrome, Mercury / Glare Chrome
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc
FORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact SLR XS:39/40cm, S:39/40cm, M:39/42cm, M/L:39/42cm, L:41/44cm, XL:41/44cm
GRIPS	Stratus Lite 2.0
STEM	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SEATPOST	Giant Variant, composite, -5/+15mm offset
SADDLE	Giant Fleet SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Force AXS
FRONT DERAILLEUR	SRAM Force AXS
REAR DERAILLEUR	SRAM Force AXS
BRAKES	SRAM Force eTap hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM Force AXS
CASSETTE	SRAM Force, 12-speed, 10x36
CHAIN	SRAM Force D1
CRANKSET	SRAM Force AXS, 33/46 with SRAM power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Giant Aero Carbon Spoke
TIRES	CADEX Race GC, tubeless, 700x28c (28mm), folding
EXTRAS	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	425	445	470	500	530	560
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,5°	73,0°	73,0°	72,5°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72	64	59	59	59	59
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	69,5	69,5	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	703	722	743	771	798	822
Handlebar Width (mm)	400	400	420	420	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	170	170	172,5	172,5	175	175
Wheel Size	700C	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.