

# TCR ADVANCED PRO 0 (AXS)

**GIANT**



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLOURS</b>	Midnight Moon, Carbon
<b>FRAME</b>	Advanced-grade Composite, 12x142mm thru-axle, disc
<b>FORK</b>	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
<b>GRIPS</b>	Stratus Lite 2.0
<b>STEM</b>	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
<b>SEATPOST</b>	Giant Variant, composite, -5/+15mm offset
<b>SADDLE</b>	Giant Fleet SL
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM Force AXS E1
<b>FRONT DERAILLEUR</b>	SRAM Force AXS E1
<b>REAR DERAILLEUR</b>	SRAM Force AXS E1
<b>BRAKES</b>	SRAM Force E1 hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
<b>BRAKE LEVERS</b>	SRAM Force AXS
<b>CASSETTE</b>	SRAM Force E1, 12-speed, 10x36
<b>CHAIN</b>	SRAM Force E1
<b>CRANKSET</b>	SRAM Force AXS E1, 35/48 with SRAM power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

WHEELS	
<b>RIMS</b>	Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm
<b>HUBS</b>	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	Giant Aero Carbon Spoke
<b>TIRES</b>	CADEX Road Race GC, tubeless, 700x30mm, folding
<b>EXTRAS</b>	computer mount, 33mm max tire size
LIMITS	
<b>MAX TIRE CLEARANCE</b>	33mm

**Suggested Retail Price (CDN): \$8,299.00**

## FRAME GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	425	445	470	500	530	560
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72.1	64	59.2	59.2	59.2	59.2
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	719	734	752	768	786	803
Handlebar Width (mm)	420	420	440	440	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172.5	172.5

All prices and specifications are subject to change without notice.