

TCR ADVANCED PRO 0 AXS



SPECS

FRAME	
SIZES	S, M, ML, L, XL
COLOURS	Gloss Ocean Twilight/Lightning Silver
FRAME	Advanced-Grade Composite 12x142mm thru-axle, Disc
FORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
COMPONENTS	
HANDLEBAR	Giant Contact SLR, 10.5 degree flare
GRIPS	Giant Stratus Lite 2.0 with gel
STEM	Giant Contact SL Aerolight
SEATPOST	Giant Variant, Composite Offset -5/+15mm
SADDLE	Giant Fleet SL 7mm SST Rail With Giant ParticleFlow technology
PEDALS	PEDALS NOT SUPPLIED
DRIVETRAIN	
SHIFTERS	SRAM Force AXS 2x12
FRONT DERAILLEUR	SRAM Force AXS
REAR DERAILLEUR	SRAM Force AXS
BRAKES	SRAM Force AXS HRD, Centreline XR 160/140mm rotors
BRAKE LEVERS	SRAM Force AXS HRD
CASSETTE	SRAM Force, XG-1270, 10X36
CHAIN	SRAM Force
CRANKSET	SRAM Force DUB 33/46 with Quarq power meter
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	New Giant SLR 0 40 Carbon Disc Wheel System with GIANT patented DBL (Dynamic Balanced Lacing) technology
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Giant Aero Carbon Spoke
TYRES	New CADEX Race GC Tubeless 700x28mm effective 170 TPI, Folding
EXTRAS	Factory tubeless set up, out front computer mount
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	425	445	470	500	530	560
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71.0°	72.3°	73.5°	73.0°	73.0°	72.5°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72	64	59	59	59	59
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	69.5	69.5	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	703	722	743	771	798	822
Handlebar Width (mm)	400	400	420	420	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	170	170	172.5	172.5	175	175
Wheel Size	700C	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.