

# TCR ADVANCED PRO 0 (AXS)\*

**GIANT**



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLORS</b>	Carbon
<b>FRAME</b>	Advanced-Grade Composite, 12x142mm thru-axle, disc
<b>FORK</b>	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR XS:37/42cm, S:37/42cm, M:39/44cm, M/L:39/44cm, L:39/44cm, XL:39/44cm
<b>GRIPS</b>	Stratus Lite 2.0
<b>STEM</b>	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
<b>SEATPOST</b>	Giant Variant, composite, -5/+15mm offset
<b>SADDLE</b>	Giant Fleet SL
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM Force AXS HRD, ED-Force-E1
<b>FRONT DERAILLEUR</b>	SRAM Force AXS, FD-Force-E-E1
<b>REAR DERAILLEUR</b>	SRAM Force AXS, RD-Force-E-E1
<b>BRAKES</b>	SRAM Force AXS HRD, ED-Force-E1, SRAM CenterLine XR rotors [F]160mm, [R]140mm
<b>BRAKE LEVERS</b>	SRAM Force AXS HRD, ED-Force-E1
<b>CASSETTE</b>	SRAM Force E1 XG-1270, 12-speed, 10-36
<b>CHAIN</b>	SRAM Force-E1, 12-speed
<b>CRANKSET</b>	SRAM Force E1 DUB, 35/48 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

WHEELS	
<b>RIMS</b>	Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm
<b>HUBS</b>	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	Giant Aero Carbon Spoke
<b>TIRES</b>	CADEX Race GC, tubeless, 700x30c (30mm), folding
<b>EXTRAS</b>	Computer mount, tubeless prepared, 33mm max tyre size
LIMITS	
<b>MAX TIRE CLEARANCE</b>	33 mm

**Price: \$9,499.00**

## GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	425	445	470	500	530	560
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72.1	64	59.2	59.2	59.2	59.2
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	719	734	752	768	786	803
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172.5	172.5

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.