

TCR ADVANCED PRO 0 (AXS)

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Midnight Moon
CUADRO	Advanced-grade Composite, 12x142mm thru-axle, disc
HORQUILLA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
AMORTIGUADOR	N/A
COMPONENTES	
MANILLAR	Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
PUÑOS	Stratus Lite 2.0
POTENCIA	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
TIJA DE SILLÍN	Giant Variant, composite, -5/+15mm offset
SILLÍN	Giant Fleet SL
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM Force AXS E1
DESVIADOR	SRAM Force AXS E1
CAMBIO TRASERO	SRAM Force AXS E1
FRENOS	SRAM Force E1 hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
PALANCAS DE FRENOS	SRAM Force AXS
CASSETTE	SRAM Force E1, 12-speed, 10x36
CADENA	SRAM Force E1
JGO. PLATOS Y BIELAS	SRAM Force AXS E1, 35/48 with SRAM power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
CAJA DE PEDALIER	SRAM DUB, press fit

RUEDAS	
LLANTAS	Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm
BUJES	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
RADIOS	Giant Aero Carbon Spoke
CUBIERTAS	CADEX Road Race GC, tubeless, 700x30mm, folding
EXTRAS	computer mount, tubeless prepared, 33mm max tire size
LÍMITES	
MÁXIMA ANCHURA DE NEUMÁTICO	33mm

Precio: 6.499,00 €

GEOMETRÍA

CUADRO	XS	S	M	ML	L	XL
Longitud del tubo del sillín (mm)	425	445	470	500	530	560
Ángulo del tubo del sillín	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Longitud del tubo superior (mm) (mm)	520	535	550	565	580	600
Longitud del tubo de dirección (mm) (mm)	120	130	145	165	185	200
Ángulo del tubo de dirección	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Inclinación de la horquilla (mm)	45	45	45	45	45	45
Trail (mm) (mm)	72,1	64	59,2	59,2	59,2	59,2
Distancia entre ejes (mm) (mm)	976	977	980	991	1006	1020
Longitud de la vaina (mm) (mm)	405	405	405	405	405	405
Caída del eje de pedalier (mm) (mm)	72	70	70	67	67	67
Stack (mm) (mm)	517	528	545	562	581	596
Reach (mm) (mm)	376	383	388	393	402	412
Altura del suelo al tubo (mm) (mm)	719	734	752	768	786	803
Ancho del manillar (mm) (mm)	420	420	440	440	440	440
Longitud de la potencia (mm) (mm)	80	90	100	110	110	120
Longitud de las bielas (mm) (mm)	165	165	170	170	172,5	172,5

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.