

TCR ADVANCED PRO 0 (AXS)

GIANT

SPECIFIKACIJE

| OKVIR | |
|---------------------|---|
| VELIČINE | XS, S, M, M/L, L, XL |
| BOJE | Midnight Moon, Carbon |
| OKVIR | Advanced-grade Composite, 12x142mm thru-axle, disc |
| VILICA | Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc |
| AMORTIZER | N/A |
| KOMPONENTE | |
| VOLAN | Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm |
| GRIPS | Stratus Lite 2.0 |
| LULA VOLANA | Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm |
| CIJEV SJEDALA | Giant Variant, composite, -5/+15mm offset |
| SJEDALO | Giant Fleet SL |
| POGON | |
| RUČICE MJENJAČA | SRAM Force AXS E1 |
| PREDNJI MJENJAČ | SRAM Force AXS E1 |
| STRAŽNJI MJENJAČ | SRAM Force AXS E1 |
| KOČNICE | SRAM Force E1 hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm |
| RUČICE KOČNICA | SRAM Force AXS |
| KAZETA | SRAM Force E1, 12-speed, 10x36 |
| LANAC | SRAM Force E1 |
| POGON | SRAM Force AXS E1, 35/48 with SRAM power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm |
| OSOVINA POGONA (BB) | SRAM DUB, press fit |

| KOTAČI | |
|--------------------|--|
| OBRUČI | Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm |
| NABE | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle |
| ŽBICE | Giant Aero Carbon Spoke |
| GUME | CADEX Road Race GC, tubeless, 700x30mm, folding |
| DODACI | computer mount, tubeless prepared, 33mm max tire size |
| LIMITS | |
| MAX TIRE CLEARANCE | 33mm |

GEOMETRIJA

| OKVIR | XS | S | M | ML | L | XL |
|--|-------|-------|-------|-------|-------|-------|
| Dužina cijevi sjedala (mm) | 425 | 445 | 470 | 500 | 530 | 560 |
| Kut cijevi sjedala | 74,5° | 74,0° | 73,5° | 73,0° | 73,0° | 72,5° |
| Dužina gornje cijevi (mm) | 520 | 535 | 550 | 565 | 580 | 600 |
| Dužina prednje cijevi (mm) | 120 | 130 | 145 | 165 | 185 | 200 |
| Kut vilice | 71,0° | 72,3° | 73,0° | 73,0° | 73,0° | 73,0° |
| Zakrivljenost vilice (offset) (mm) | 45 | 45 | 45 | 45 | 45 | 45 |
| Staza (mm) | 72,1 | 64 | 59,2 | 59,2 | 59,2 | 59,2 |
| Međuosovinski razmak kotača (mm) | 976 | 977 | 980 | 991 | 1006 | 1020 |
| Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm) | 405 | 405 | 405 | 405 | 405 | 405 |
| Položaj osovine pogona (mm) | 72 | 70 | 70 | 67 | 67 | 67 |
| Vertikalna dužina od osovine pogona do glave okvira (stack) (mm) | 517 | 528 | 545 | 562 | 581 | 596 |
| Horizontalna dužina od osovine pogona do glave okvira (reach) (mm) | 376 | 383 | 388 | 393 | 402 | 412 |
| Prekoračna visina (mm) | 719 | 734 | 752 | 768 | 786 | 803 |
| Širina volana (mm) | 420 | 420 | 440 | 440 | 440 | 440 |
| Dužina lule volana (mm) | 80 | 90 | 100 | 110 | 110 | 120 |
| Dužina poluge pedale (mm) | 165 | 165 | 170 | 170 | 172,5 | 172,5 |

Sve navedene specifikacije podložne su promjeni bez prethodne najave.