

TCR ADVANCED PRO 0 (AXS)

GIANT



SPECS

QUADRO	
TAMANHOS	XS, S, M, M/L, L, XL
CORES	Midnight Moon
QUADRO	Advanced-grade Composite, 12x142mm thru-axle, disc
FORQUILHA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
AMORTECEDORES	N/A
COMPONENTES	
GUIADOR	Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
PUNHOS	Stratus Lite 2.0
AVANÇO	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
ESPIGÃO DE SELIM	Giant Variant, composite, -5/+15mm offset
SELIM	Giant Fleet SL
TRANSMISSÃO	
MANETES	SRAM Force AXS E1
DESVIADOR DIANTEIRO	SRAM Force AXS E1
DESVIADOR TRASEIRO	SRAM Force AXS E1
TRAVÕES	SRAM Force E1 hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
MANÍPULOS DOS TRAVÕES	SRAM Force AXS
CASSETE	SRAM Force E1, 12-speed, 10x36
CORRENTE	SRAM Force E1
CONJUNTO PEDALEIRO	SRAM Force AXS E1, 35/48 with SRAM power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
MOVIMENTO CENTRAL	SRAM DUB, press fit

RODAS	
AROS	Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm
CUBOS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
RAIOS	Giant Aero Carbon Spoke
PNEUS	CADEX Road Race GC, tubeless, 700x30mm, folding
EXTRAS	computer mount, tubeless prepared, 33mm max tire size
LIMITES	
FOLGA MÁXIMA DO PNEU	33mm

Preço: 5 699,00 €

GEOMETRIA

QUADRO	XS	S	M	ML	L	XL
Comprimento do tubo do assento (mm)	425	445	470	500	530	560
Ângulo do tubo do assento	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Comprimento do tubo superior (mm)	520	535	550	565	580	600
Comprimento do tubo principal (mm)	120	130	145	165	185	200
Ângulo do tubo principal	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Garfo ancinho (mm)	45	45	45	45	45	45
Trilha (mm)	72,1	64	59,2	59,2	59,2	59,2
distância entre eixos (mm)	976	977	980	991	1006	1020
Comprimento Chain Stay (mm)	405	405	405	405	405	405
Suporte inferior (mm)	72	70	70	67	67	67
Pilha (mm)	517	528	545	562	581	596
Alcançar (mm)	376	383	388	393	402	412
Altura do standover (mm)	719	734	752	768	786	803
Largura do guidão (mm)	420	420	440	440	440	440
Comprimento da haste (mm)	80	90	100	110	110	120
Comprimento da Manivela (mm)	165	165	170	170	172,5	172,5

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.