

TCR ADVANCED PRO 0 (AXS)

GIANT

SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Midnight Moon, Carbon
OKVIR	Advanced-grade Composite, 12x142mm thru-axle, disc
VILICE	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
GRIPS	Stratus Lite 2.0
OPORA KRMILA	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
OPORA SEDEŽA	Giant Variant, composite, -5/+15mm offset
SEDEŽ	Giant Fleet SL
POGON	
PRESTAVNE ROČICE	SRAM Force AXS E1
PREDNJI MENJALNIK	SRAM Force AXS E1
ZADNJI MENJALNIK	SRAM Force AXS E1
ZAVORE	SRAM Force E1 hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
ZAVORNE ROČICE	SRAM Force AXS
VERIŽNIK	SRAM Force E1, 12-speed, 10x36
VERIGA	SRAM Force E1
GONILKE Z VERIŽNIKI	SRAM Force AXS E1, 35/48 with SRAM power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm
PESTA	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
NAPERE	Giant Aero Carbon Spoke
PLAŠČI	CADEX Road Race GC, tubeless, 700x30mm, folding
DODATKI	computer mount, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	425	445	470	500	530	560
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Višina glave okvirja (mm)	120	130	145	165	185	200
Krmlini kot	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Zamik vpetja osi (mm)	45	45	45	45	45	45
Trail (mm)	72,1	64	59,2	59,2	59,2	59,2
Medosna razdalja (mm)	976	977	980	991	1006	1020
Dolžina cevi ob verigi (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Oddaljenost zgornje cevi od gonilne osi (mm)	517	528	545	562	581	596
Doseg (mm)	376	383	388	393	402	412
Višina zgornje cevi (mm)	719	734	752	768	786	803
Širina krmila (mm)	420	420	440	440	440	440
Dolžina opore krmila (mm)	80	90	100	110	110	120
Dolžina gonilke (mm)	165	165	170	170	172,5	172,5

Vse navedene specifikacije se lahko spremenijo brez obvestila.