

TCR ADVANCED PRO 0-DI2

GIANT



SPECIFIKATIONER

RAMME	
RAMME	Advanced-Grade Composite, 12x142mm thru-axle, Disc
FORGAFFEL	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
KOMPONENTER	
STYR	Giant Contact SLR
GREB / STYRBÅND	Stratus Lite 2.0 w/ gel
FREMPIND	Giant Contact SL Aerolight, -10 degree
SADELPIND	Giant Variant, Composite Offset -5/+15mm
SADEL	Giant Fleet SL 7mm SST Rail With Giant ParticleFlow technology
PEDALER	GCS,GTS:Platform Pedal Rest GSC : no pedal
STYRFITTINGS	HS-GT-01
GEARGRUPPE	
SKIFTEGREB	Shimano Ultegra Di2 HRD
FORSKIFTER	Shimano Ultegra Di2
BAGSKIFTER	Shimano Ultegra Di2
BREMSE	Shimano Ultegra Di2 HRD
BREMSEGREB	Shimano Ultegra Di2 HRD
KASSETTE	Shimano CS-R8100 11x34, 12-speed
KÆDE	Shimano CN-M8100, 12-speed
KRANKSÆT	Shimano Ultegra, 36/52 with Giant Power Pro power meter
KRANKBOKS	Shimano, PressFit 71

HJUL	
FÆLGE	Giant SLR 0 40 Carbon Disc Wheel System with Giant patented DBL (Dynamic Balanced Lacing) technology
NAV	Giant SLR 0 40 Carbon Disc Wheel System with Giant patented DBL (Dynamic Balanced Lacing) technology
EGER	Giant SLR 0 40 Carbon Disc Wheel System with Giant patented DBL (Dynamic Balanced Lacing) technology
DÆK	CADEX Road Race GC Tubeless 700x30mm 240 TPI, Folding
EKSTRA	Computer mount, tubeless prepared
GRÆNSER	
MAX DÆKSTØRRELSE	700x33mm

Pris: 51.609,00 kr.

GEOMETRI

RAMME	S	M	ML	L	XL
Sadelrørsvinkel	74,0°	73,5°	73,0°	73,0°	72,5°
Overrørs længde (mm)	535	550	565	580	600
Kronrørs længde (mm)	130	145	165	185	200
Kronrørsvinkel	72,3°	73,0°	73,0°	73,0°	73,0°
Akselafstand (mm)	977	980	991	1006	1020
Kædestagslængde (mm)	405	405	405	405	405
Stack (mm)	528	545	562	581	596
Reach (mm)	383	388	393	402	412
Skridthøjde (mm)	734	752	768	786	803
Pedalarmslængde (mm)	165	170	170	172,5	172,5

Alle de anførte specifikationer kan ændres uden varsel.