

TCR ADVANCED PRO 0 DI2

GIANT



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Ocean Twilight / Glare Chrome, Mercury / Glare Chrome
RAHMEN	Advanced-Grade Composite, 12x142mm thru-axle, disc
GABEL	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTEN	
LENKER	Giant Contact SLR XS:39/40cm, S:39/40cm, M:39/42cm, M/L:39/42cm, L:41/44cm, XL:41/44cm
GRIFFE	Stratus Lite 2.0
VORBAU	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SATTELSTÜTZE	Giant Variant, composite, -5/+15mm offset
SATTEL	Giant Fleet SL
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	Shimano Ultegra Di2
UMWERFER	Shimano Ultegra Di2 FD-R8150
SCHALTWERK	Shimano Ultegra Di2 RD-R8150
BREMSEN	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
BREMSEBEL	Shimano Ultegra Di2
KASSETTE	Shimano Ultegra, 12-speed, 11x34
KETTE	Shimano CN-M8100
KURBEL	Shimano Ultegra, 36/52 with Giant Power Pro power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
TRETLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm
NABE	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
SPEICHEN	Giant Aero Carbon Spoke
REIFEN	CADEX Race GC, tubeless, 700x28c (28mm), folding
EXTRAS	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
Sitzrohrlänge (mm)	425	445	470	500	530	560
Sitzrohrwinkel	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Oberrohrlänge (mm)	520	535	550	565	580	600
Steuerrohr-Länge (mm)	120	130	145	165	185	200
Steuerrohr-Winkel	71.0°	72.3°	73.5°	73.0°	73.0°	72.5°
Gabelneigung (mm)	45	45	45	45	45	45
Trail (mm)	72	64	59	59	59	59
Radstand (mm)	976	977	980	991	1006	1020
Kettenstreben-Länge (mm)	405	405	405	405	405	405
Tretlager-Höhe (mm)	72	69.5	69.5	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Überstandshöhe (mm)	703	722	743	771	798	822
Lenkerbreite (mm)	400	400	420	420	440	440
Vorbaulänge (mm)	80	90	100	110	110	120
Kurbellänge (mm)	170	170	172.5	172.5	175	175
Radgrösse	700C	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.