

TCR ADVANCED PRO 0 DI2

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Mercury / Glare Chrome
CUADRO	Advanced-Grade Composite, 12x142mm thru-axle, disc
HORQUILLA	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTES	
MANILLAR	Giant Contact SLR XS:39/40cm, S:39/40cm, M:39/42cm, M/L:39/42cm, L:41/44cm, XL:41/44cm
PUÑOS	Stratus Lite 2.0
POTENCIA	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
TIJA DE SILLÍN	Giant Variant, composite, -5/+15mm offset
SILLÍN	Giant Fleet SL
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Ultegra Di2
DESVIADOR	Shimano Ultegra Di2 FD-R8150
CAMBIO TRASERO	Shimano Ultegra Di2 RD-R8150
FRENOS	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
PALANCAS DE FRENOS	Shimano Ultegra Di2
CASSETTE	Shimano Ultegra, 12-speed, 11x34
CADENA	Shimano CN-M8100
JGO. PLATOS Y BIELAS	Shimano Ultegra, 36/52 with Giant Power Pro power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
CAJA DE PEDALIER	Shimano, press fit

RUEDAS	
LLANTAS	Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm
BUJES	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
RADIOS	Giant Aero Carbon Spoke
CUBIERTAS	CADEX Race GC, tubeless, 700x28c (28mm), folding
EXTRAS	computer mount, tubeless prepared, 33mm max tire size
LÍMITES	
MÁXIMA ANCHURA DE NEUMÁTICO	33mm

Precio: 6.499,00 €

GEOMETRÍA

CUADRO	XS	S	M	ML	L	XL
Longitud del tubo del sillín (mm)	425	445	470	500	530	560
Ángulo del tubo del sillín	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Longitud del tubo superior (mm) (mm)	520	535	550	565	580	600
Longitud del tubo de dirección (mm) (mm)	120	130	145	165	185	200
Ángulo del tubo de dirección	71,0°	72,3°	73,5°	73,0°	73,0°	72,5°
Inclinación de la horquilla (mm)	45	45	45	45	45	45
Trail (mm) (mm)	72	64	59	59	59	59
Distancia entre ejes (mm) (mm)	976	977	980	991	1006	1020
Longitud de la vaina (mm) (mm)	405	405	405	405	405	405
Caída del eje de pedalier (mm) (mm)	72	69,5	69,5	67	67	67
Stack (mm) (mm)	517	528	545	562	581	596
Reach (mm) (mm)	376	383	388	393	402	412
Altura del suelo al tubo (mm) (mm)	703	722	743	771	798	822
Ancho del manillar (mm) (mm)	400	400	420	420	440	440
Longitud de la potencia (mm) (mm)	80	90	100	110	110	120
Longitud de las bielas (mm) (mm)	170	170	172,5	172,5	175	175
Tamaño de ruedas	700C	700C	700C	700C	700C	700C

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.