

TCR ADVANCED PRO 0 DI2



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Ocean Twilight / Glare Chrome, Mercury / Glare Chrome
CUADRO	Advanced-Grade Composite, 12x142mm thru-axle, disc
TIJERA	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTES	
MANUBRIO	Giant Contact SLR XS:39/40cm, S:39/40cm, M:39/42cm, M/L:39/42cm, L:41/44cm, XL:41/44cm
GRIPS	Stratus Lite 2.0
POTENCIA	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
POSTE DE ASIENTO	Giant Variant, composite, -5/+15mm offset
ASIENTO	Giant Fleet SL
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Ultegra Di2
DESVIADOR	Shimano Ultegra Di2 FD-R8150
CAMBIO TRASERO	Shimano Ultegra Di2 RD-R8150
FRENOS	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
PALANCAS DE FRENOS	Shimano Ultegra Di2
CASSETTE	Shimano Ultegra, 12-speed, 11x34
CADENA	Shimano CN-M8100
MULTIPLICACIÓN	Shimano Ultegra, 36/52 with Giant Power Pro power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
EJE DE CENTRO	Shimano, press fit

RUEDAS	
RUEDAS	Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm
MAZAS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
RAYOS	Giant Aero Carbon Spoke
NEUMÁTICOS	CADEX Race GC, tubeless, 700x28c (28mm), folding
EXTRAS	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

Precio: \$149,990.00

GEOMETRÍA

CUADRO	XS	S	M	ML	L
Longitud de la Base del Poste de Asiento (mm)	425	445	470	500	530
Ángulo de la Base del Poste de Asiento	74.5°	74.0°	73.5°	73.0°	73.0°
Longitud del Tubo Superior (mm)	520	535	550	565	580
Longitud del Telescopio (mm)	120	130	145	165	185
Ángulo del Telescopio	71.0°	72.3°	73.5°	73.0°	73.0°
Rake (mm)	45	45	45	45	45
Trail (mm)	72	64	59	59	59
Distancia entre Ejes (mm)	976	977	980	991	1006
Longitud de Vaina Inferior (mm)	405	405	405	405	405
Caída del Eje de Centro (mm)	72	69.5	69.5	67	67
Stack (mm)	517	528	545	562	581
Reach (mm)	376	383	388	393	402
Altura del Tubo Superior al Suelo (mm)	703	722	743	771	798
Ancho del Manubrio (mm)	400	400	420	420	440
Longitud de la Potencia (mm)	80	90	100	110	110
Longitud de la Biela (mm)	170	170	172.5	172.5	175
Tamaño de las Ruedas	700C	700C	700C	700C	700C

Todas las especificaciones están sujetas a cambios sin previo aviso.