



SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	XS, S, M, M/L, L, XL
ΧΡΩΜΑΤΑ	Carbon
ΣΚΕΛΕΤΟΣ	Advanced-grade Composite, 12x142mm thru-axle, disc
ΠΙΡΟΥΝΙ	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
ΑΝΑΡΤΗΣΗ	N/A
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
GRIPS	Stratus Lite 2.0
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
ΛΑΙΜΟΣ ΣΈΛΛΑΣ	Giant Variant, composite, -5/+15mm offset
ΣΈΛΛΑ	Giant Fleet SL
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	Shimano Ultegra Di2
ΝΤΕΡΑΓΓΙΕΡ ΕΜΠΡΟΣΘΙΟ	Shimano Ultegra Di2 FD-R8150
ΝΤΕΡΑΓΓΙΕΡ ΟΠΙΣΘΙΟ.	Shimano Ultegra Di2 RD-R8150
ΦΡΈΝΑ	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
ΜΑΝΈΤΤΕΣ ΦΡΈΝΩΝ	Shimano Ultegra Di2
CASETTE Ή ΕΛΕΥΘΕΡΟ	Shimano Ultegra, 12-speed, 11x34
ΑΛΥΣΙΔΑ	Shimano CN-M8100
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	Shimano Ultegra, 30/54 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm
ΚΈΝΤΡΑ	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
ΑΚΤΙΝΕΣ	Giant Aero Carbon Spoke
ΕΛΑΣΤΙΚΑ	CADEX Road Race GC, tubeless, 700x30mm, folding
EXTRAS	computer mount, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	XS	S	M	ML	L	XL
Seat Tube Length (mm)	425	445	470	500	530	560
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72,1	64	59,2	59,2	59,2	59,2
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	719	734	752	768	786	803
Handlebar Width (mm)	420	420	440	440	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172,5	172,5

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση