

TCR ADVANCED PRO 1 (AXS)

GIANT



СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XS, S, M, M/L, L, XL
ЦВЯТ	Tech Silver
РАМКА	Advanced-grade Composite, 12x142mm thru-axle, disc
ВИЛКА	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact SL XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
ГРИПОВЕ	Stratus Lite 2.0
ЛАПА	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
КОЛЧЕ ЗА СЕДАЛКА	Giant Variant, composite, -5/+15mm offset
СЕДАЛКА	Giant Fleet SL
DRIVETRAIN	
КОМАНДИ	SRAM Rival AXS E1
ПРЕДЕН ДЕРАЙЛЪОР	SRAM Rival AXS E1
ЗАДЕН ДЕРАЙЛЪОР	SRAM Rival AXS E1
СПИРАЧКИ	SRAM Rival E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	SRAM Rival AXS
КАСЕТА	SRAM Rival E1, 12-speed, 10x36
ВЕРИГА	SRAM Rival E1
КУРБЕЛ	SRAM Rival DUB, 35/48 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
СРЕДНА КАСЕТА	SRAM DUB, press fit

КАПЛИ	
ШИНИ	Giant SLR 1 40 WheelSystem, [F]40mm, [R]40mm
ГЛАВИНИ	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
СПИЦИ	Sapim
ГУМИ	Giant Gavia Course 0, tubeless, 700x28c (28mm), folding
ЕКСТРИ	computer mount, tubeless prepared, 33mm max tire size
ЛИМИТИ	
MAX TIRE CLEARANCE	33mm

ГЕОМЕТРИЯ

РАМКА	XS	S	M	ML	L	XL
Seat Tube Length (mm)	425	445	470	500	530	560
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72,1	64	59,2	59,2	59,2	59,2
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Обсер (mm)	376	383	388	393	402	412
Stand Over Height (mm)	719	734	752	768	786	803
Ширина на Кормило (mm)	420	420	440	440	440	440
Дължина на Лапа (mm)	80	90	100	110	110	120
Дължина на Курбел (mm)	165	165	170	170	172,5	172,5

All specifications listed are subject to change without notice.