

TCR ADVANCED PRO 1 (AXS)



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Tech Silver
FRAME	Advanced-grade Composite, 12x142mm thru-axle, disc
FORK	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact SL XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
GRIPS	Stratus Lite 2.0
STEM	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SEATPOST	Giant Variant, composite, -5/+15mm offset
SADDLE	Giant Fleet SL
DRIVETRAIN	
SHIFTERS	SRAM Rival AXS E1
FRONT DERAILLEUR	SRAM Rival AXS E1
REAR DERAILLEUR	SRAM Rival AXS E1
BRAKES	SRAM Rival E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM Rival AXS
CASSETTE	SRAM Rival E1, 12-speed, 10x36
CHAIN	SRAM Rival E1
CRANKSET	SRAM Rival DUB, 35/48 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant SLR 1 40 WheelSystem, [F]40mm, [R]40mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim
TIRES	Giant Gavia Course 0, tubeless, 700x28c (28mm), folding
EXTRAS	computer mount, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	425	445	470	500	530	560
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72,1	64	59,2	59,2	59,2	59,2
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	719	734	752	768	786	803
Handlebar Width (mm)	420	420	440	440	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172,5	172,5

All specifications listed are subject to change without notice.