

TCR ADVANCED PRO 1 AXS



SPECIFICATIES

FRAME	
MATEN	XS, S, M, M/L, L, XL
KLEUREN	Carbon / Chrome
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc
VOORVORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
ONDERDELEN	
STUUR	Giant Contact SL XS:39/40cm, S:39/40cm, M:39/42cm, M/L:39/42cm, L:41/44cm, XL:41/44cm
HANDVATTEN	Stratus Lite 2.0
STUURPEN	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
ZADELLEN	Giant Variant, composite, -5/+15mm offset
ZADEL	Giant Fleet SL
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	SRAM Rival AXS
VOORDERAILLEUR	SRAM Rival AXS
ACHTERDERAILLEUR	SRAM Rival AXS
REMMEN	SRAM Rival eTap hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
REMHENDELS	SRAM Rival AXS
CASSETTE	SRAM Rival, 12-speed, 10x36
AANDRIJVING	SRAM Rival D1
CRANKSET	SRAM Rival, 35/48 with Giant Power Halo power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant SLR 1 40 WheelSystem, [F]40mm, [R]40mm
NAVEN	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	Sapim CX-Ray
BANDEN	Giant Gavia Course 0, tubeless, 700x25c (28mm), folding
EXTRA'S	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

Adviesprijs: € 5.099,00

GEOMETRIE

FRAME	S	M	ML	L	XL
Zitbuis lengte (mm)	445	470	500	530	560
Zitbuis hoek	74,0°	73,5°	73,0°	73,0°	72,5°
Frame Lengte (horizontaal) (mm)	535	550	565	580	600
Balhoofdbuis Lengte (mm)	130	145	165	185	200
Balhoofdbuis Hoek	72,3°	73,5°	73,0°	73,0°	72,5°
Vork Sprong (mm)	45	45	45	45	45
Naloop (mm)	64	59	59	59	59
Wielbasis (mm)	977	980	991	1006	1020
Liggende achtersvork lengte (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	69,5	69,5	67	67	67
Stack (mm)	528	545	562	581	596
Reach (mm)	383	388	393	402	412
Stand Over Height (mm)	722	743	771	798	822
Stuur breedte (mm)	400	420	420	440	440
Stuurpen Lengte (mm)	90	100	110	110	120
Cranklengte (mm)	170	172,5	172,5	175	175
Wielmaat	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.