

TCR ADVANCED PRO 1 (AXS)

GIANT



SPECS

CADRU	
MARIMI	XS, S, M, M/L, L, XL
CULORI	Tech Silver
CADRU	Advanced-grade Composite, 12x142mm thru-axle, disc
FURCA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTE	
GHIDON	Giant Contact SL XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
GRIPS	Stratus Lite 2.0
PIPA	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
TIJA SA	Giant Variant, composite, -5/+15mm offset
SA	Giant Fleet SL
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	SRAM Rival AXS E1
SCHIMBATOR FATA	SRAM Rival AXS E1
SCHIMBATOR SPATE	SRAM Rival AXS E1
FRANE	SRAM Rival E1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
MANETE FRANA	SRAM Rival AXS
PINIOANE	SRAM Rival E1, 12-speed, 10x36
LANT	SRAM Rival E1
ANGRENAJ	SRAM Rival DUB, 35/48 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

ROTI	
JANTE	Giant SLR 1 40 WheelSystem, [F]40mm, [R]40mm
BUTUCI	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
SPITE	Sapim
ANVELOPE	Giant Gavia Course 0, tubeless, 700x28c (28mm), folding
EXTRAS	computer mount, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRIE

CADRU	XS	S	M	ML	L	XL
Seat Tube Length (mm)	425	445	470	500	530	560
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72,1	64	59,2	59,2	59,2	59,2
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	719	734	752	768	786	803
Handlebar Width (mm)	420	420	440	440	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172,5	172,5

Toate specificatiile enumerate se pot schimba fara notificare prealabila.