

TCR ADVANCED PRO 1 (AXS)

GIANT



產品規格

車架	
尺寸	XS, S, M, M/L
顏色	科技銀
車架	Advanced-grade Composite, 12x142mm thru-axle, disc
前叉	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
車把手	Giant Contact SL
把手帶/套	Stratus Lite 2.0
豎桿	Giant Contact SL AeroLight
座桿	Giant Variant, composite, -5/+15mm offset
坐墊	Giant Fleet SL
DRIVETRAIN	
變速把手	SRAM Rival AXS E1
前變速器	SRAM Rival AXS E1
後變速器	SRAM Rival AXS E1
煞車系統	SRAM Rival E1 hydraulic,
煞車把手	SRAM Rival AXS
飛輪	SRAM Rival E1, 12-speed, 10x36t
鍊條	SRAM Rival E1
大齒盤	SRAM Rival DUB, 35/48 with power meter
BOTTOM BRACKET (B B)	SRAM DUB, press fit

輪組	
輪圈	Giant SLR 1 40 WheelSystem,
花鼓	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
輻條	Sapim
外胎	Giant Gavia Course 0, tubeless, 700x28c (28mm), folding
其他	computer mount, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

Price: NT\$138,000

車架幾何

車架	XS	S	M	ML
座(立)管長 (mm)	425	445	470	500
座(立)管角度	74.5°	74.0°	73.5°	73.0°
上管長度 (mm)	520	535	550	565
頭管長度 (mm)	120	130	145	165
頭管角度	71.0°	72.3°	73.0°	73.0°
前叉 (mm)	45	45	45	45
Trail (mm)	72.1	64	59.2	59.2
前後輪距 (mm)	976	977	980	991
後下叉長度 (mm)	405	405	405	405
五通下降高度 (mm)	72	70	70	67
頭碗至五通高度 (mm)	517	528	545	562
頭碗至五通長度 (mm)	376	383	388	393
上管至地面高度 (mm)	719	734	752	768
把手寬 (mm)	420	420	440	440
龍頭長度 (mm)	80	90	100	110
曲柄長度 (mm)	165	165	170	170

*捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。