

TCR ADVANCED PRO 1 DI2

GIANT



SPECIFIKATIONER

RAMME	
STØRRELSER	XS, S, M, M/L, L, XL
FARVER	Carbon / Chrome
RAMME	Advanced-Grade Composite, 12x142mm thru-axle, disc
FORGAFFEL	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYR	Giant Contact SL XS:39/40cm, S:39/40cm, M:39/42cm, M/L:39/42cm, L:41/44cm, XL:41/44cm
GREB / STYRBÅND	Stratus Lite 2.0
FREMPIND	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SADELPIND	Giant Variant, composite, -5/+15mm offset
SADEL	Giant Fleet SL
PEDALER	N/A
GEARGRUPPE	
SKIFTEGREB	Shimano 105 Di2
FORSKIFTER	Shimano 105 Di2 FD-R8150
BAGSKIFTER	Shimano 105 Di2 RD-R8150
BREMSE	Shimano 105 Di2 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]140mm
BREMSEGREB	Shimano 105 Di2
KASSETTE	Shimano 105, 12-speed, 11x34
KÆDE	KMC X12L-1
KRANKSÆT	Shimano 105, 36/52 with Giant Power Pro power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
KRANKBOKS	Shimano, press fit

HJUL	
FÆLGE	Giant SLR 1 40 WheelSystem, [F]40mm, [R]40mm
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
EGER	Sapim CX-Ray
DÆK	Giant Gavia Course 0, tubeless, 700x25c (28 mm), folding
EKSTRA	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
GRÆNSER	
MAX DÆKSTØRRELSE	33mm

Pris: 37.999,00 kr.

GEOMETRI

RAMME	S	M	ML	L	XL
Sadelrørs længde (mm)	445	470	500	530	560
Sadelrørs vinkel	74,0°	73,5°	73,0°	73,0°	72,5°
Overrørs længde (mm)	535	550	565	580	600
Kronrørs længde (mm)	130	145	165	185	200
Kronrørs vinkel	72,3°	73,5°	73,0°	73,0°	72,5°
Forgaffel fremspring (rake) (mm)	45	45	45	45	45
Sti (mm)	64	59	59	59	59
Akselafstand (mm)	977	980	991	1006	1020
Kædestags længde (mm)	405	405	405	405	405
Krankboks drop (mm)	69,5	69,5	67	67	67
Stack (mm)	528	545	562	581	596
Reach (mm)	383	388	393	402	412
Skridthøjde (mm)	722	743	771	798	822
Styrbredde (mm)	400	420	420	440	440
Frempindslængde (mm)	90	100	110	110	120
Pedalarmslængde (mm)	170	172,5	172,5	175	175
Hjulstørrelse	700C	700C	700C	700C	700C

Alle de anførte specifikationer kan ændres uden varsel.