

TCR ADVANCED PRO 1 (DI2)

GIANT



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, M/L, L, XL
FARVER	Tech Silver
RAMME	Advanced-grade Composite, 12x142mm thru-axle, disc
FORGAFFEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYR	Giant Contact SL XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
GREB / STYRBÅND	Stratus Lite 2.0
FREMPIND	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SADELPIND	Giant Variant, composite, -5/+15mm offset
SADEL	Giant Fleet SL
GEARGRUPPE	
SKIFTEGREB	Shimano 105 Di2
FORSKIFTER	Shimano 105 Di2 FD-R7150
BAGSKIFTER	Shimano 105 Di2 RD-R7150
BREMSE	Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors [F]160mm, [R]140mm
BREMSEGREB	Shimano 105 Di2
KASSETTE	Shimano 105, 12-speed, 11x34
KÆDE	KMC X12L-1
KRANKSÆT	Shimano 105, 36/52 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
KRANKBOKS	Shimano, press fit

HJUL	
FÆLGE	Giant SLR 1 40 WheelSystem, [F]40mm, [R]40mm
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
EGER	Sapim
DÆK	Giant Gavia Course 0, tubeless, 700x28c (28mm), folding
EKSTRA	computer mount, tubeless prepared, 33mm max tire size
GRÆNSER	
MAX DÆKSTØRRELSE	33mm

Pris: 38.999,00 kr.

GEOMETRI

RAMME	S	M	ML	L	XL
Sadelrørslængde (mm)	445	470	500	530	560
Sadelrøsvinkel	74,0°	73,5°	73,0°	73,0°	72,5°
Overrørslængde (mm)	535	550	565	580	600
Kronrørslængde (mm)	130	145	165	185	200
Kronrøsvinkel	72,3°	73,0°	73,0°	73,0°	73,0°
Forgaffel fremspring (rake) (mm)	45	45	45	45	45
Sti (mm)	64	59,2	59,2	59,2	59,2
Akselafstand (mm)	977	980	991	1006	1020
Kædestagslængde (mm)	405	405	405	405	405
Krankboks drop (mm)	70	70	67	67	67
Stack (mm)	528	545	562	581	596
Reach (mm)	383	388	393	402	412
Skridthøjde (mm)	734	752	768	786	803
Styrbredde (mm)	420	440	440	440	440
Frempindslængde (mm)	90	100	110	110	120
Pedalarmslængde (mm)	165	170	170	172,5	172,5

Alle de anførte specifikationer kan ændres uden varsel.