

# TCR ADVANCED PRO 1 (DI2)

GIANT



## TEKNISET TIEDOT

RUNKO	
KOOT	XS, S, M, M/L, L, XL
VÄRIT	Tech Silver
RUNKO	Advanced-grade Composite, 12x142mm thru-axle, disc
HAARUKKA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTIT	
OHJAUSTANKO	Giant Contact SL XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
GRIPIT	Stratus Lite 2.0
OHJAINKANNATIN	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SATULATOLPPA	Giant Variant, composite, -5/+15mm offset
SÄTULA	Giant Fleet SL
VOIMANSIIRTO	
VAIHDEVIPU	Shimano 105 Di2
ETUVAIHTAJA	Shimano 105 Di2 FD-R7150
TAKAVAIHTAJA	Shimano 105 Di2 RD-R7150
JARRUT	Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors [F]160mm, [R]140mm
JARRUKAIVAT	Shimano 105 Di2
RÄTÄSPAKKA	Shimano 105, 12-speed, 11x34
KETJUT	KMC X12L-1
KAMPISARJA	Shimano 105, 36/52 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
KESKIÖ	Shimano, press fit

RENKAAT	
VANTEET	Giant SLR 1 40 WheelSystem, [F]40mm, [R]40mm
NAVAT	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
PINNAT	Sapim
RENKAAT	Giant Gavia Course 0, tubeless, 700x28c (28mm), folding
LISÄTIEDOT	computer mount, tubeless prepared, 33mm max tire size
RAJOITTEET	
MAX RENGASVARA	33mm

Suositusuhinta: 5 199,00 €

## GEOMETRIA

RUNKO	S	M	ML	L	XL
Satulaputken pituus (mm)	445	470	500	530	560
Satulaputken kulma	74,0°	73,5°	73,0°	73,0°	72,5°
Vaakaputken pituus (mm)	535	550	565	580	600
Emäputken pituus (mm)	130	145	165	185	200
Emäputken kulma	72,3°	73,0°	73,0°	73,0°	73,0°
Haarukan offset (mm)	45	45	45	45	45
Trail-mitta (mm)	64	59,2	59,2	59,2	59,2
Akseliväli (mm)	977	980	991	1006	1020
Takahaarukan alaputken pituus (mm)	405	405	405	405	405
Keskiön pudotus (mm)	70	70	67	67	67
Stack-mitta (mm)	528	545	562	581	596
Reach-mitta (mm)	383	388	393	402	412
Standover-mitta (mm)	734	752	768	786	803
Ohjaustangon leveys (mm)	420	440	440	440	440
Ohjainkannattimen pituus (mm)	90	100	110	110	120
Kammen pituus (mm)	165	170	170	172,5	172,5

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.