

TCR ADVANCED PRO 1 Di2



SPECIFICATIES

FRAME	
MATEN	S, M, M/L, L, XL
KLEUREN	Tech Silver
FRAME	Advanced-grade Composite, 12x142mm thru-axle, disc
VOORVORK	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
ONDERDELEN	
STUUR	Giant Contact SL XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
HANDVATTEN	Stratus Lite 2.0
STUURPEN	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
ZADELPEN	Giant Variant, composite, -5/+15mm offset
ZADEL	Giant Fleet SL
AFMONTAGE	
SHIFTERS	Shimano 105 Di2
VOORDERAILLEUR	Shimano 105 Di2 FD-R7150
ACHTERDERAILLEUR	Shimano 105 Di2 RD-R7150
REMMEN	Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors [F]160mm, [R]140mm
REMHENDELS	Shimano 105 Di2
CASSETTE	Shimano 105, 12-speed, 11x34
AANDRIJVING	KMC X12L-1
CRANKSET	Shimano 105, 36/52 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant SLR 1 40 WheelSystem, [F]40mm, [R]40mm
NAVEN	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	Sapim
BANDEN	Giant Gavia Course 0, tubeless, 700x28c (28mm), folding
EXTRA'S	computer mount, tubeless prepared, 33mm max tire size
LIMITS	
MAXIMALE BANDENVRIJHEID	33mm

Adviesprijs: € 4.899,00

GEOMETRIE

FRAME	S	M	ML	L	XL
Zitbuis Lengte (mm)	445	470	500	530	560
Zitbuis Hoek	74,0°	73,5°	73,0°	73,0°	72,5°
Frame Lengte (horizontaal) (mm)	535	550	565	580	600
Balhoofdbuis Lengte (mm)	130	145	165	185	200
Balhoofdbuis Hoek	72,3°	73,0°	73,0°	73,0°	73,0°
Vork Sprong (mm)	45	45	45	45	45
Naloop (mm)	64	59,2	59,2	59,2	59,2
Wielbasis (mm)	977	980	991	1006	1020
Liggende achtersvork lengte (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	70	70	67	67	67
Stack (mm)	528	545	562	581	596
Reach (mm)	383	388	393	402	412
Stand Over Height (mm)	734	752	768	786	803
Stuur breedte (mm)	420	440	440	440	440
Stuurpen Lengte (mm)	90	100	110	110	120
Cranklengte (mm)	165	170	170	172,5	172,5

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.