

TCR ADVANCED PRO 1 (DI2)

GIANT



SPECS

| RAMME | |
|----------------|--|
| STØRRELSE | XS, S, M, M/L, L, XL |
| FARGE | Tech Silver |
| RAMME | Advanced-grade Composite, 12x142mm thru-axle, disc |
| GAFFEL | Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc |
| KOMPONENTER | |
| STYRE | Giant Contact SL XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm |
| GRIPS | Stratus Lite 2.0 |
| STYRSTEM | Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm |
| SETEPINNE | Giant Variant, composite, -5/+15mm offset |
| SADEL | Giant Fleet SL |
| DRIVVERK | |
| GIRHENDLER | Shimano 105 Di2 |
| FRONTGIR | Shimano 105 Di2 FD-R7150 |
| BAKGIR | Shimano 105 Di2 RD-R7150 |
| BREMSE | Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors [F]160mm, [R]140mm |
| BREMSEHENDLER | Shimano 105 Di2 |
| KASSETT | Shimano 105, 12-speed, 11x34 |
| KJEDE | KMC X12L-1 |
| KRANK | Shimano 105, 36/52 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm |
| BOTTOM BRACKET | Shimano, press fit |

| HJUL | |
|--------------------|--|
| FELG | Giant SLR 1 40 WheelSystem, [F]40mm, [R]40mm |
| NAV | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle |
| EIKE | Sapim |
| DEKK | Giant Gavia Course 0, tubeless, 700x28c (28mm), folding |
| EXTRAS | computer mount, tubeless prepared, 33mm max tire size |
| LIMITS | |
| MAX TIRE CLEARANCE | 33mm |

GEOMETRI

| RAMME | XS | S | M | ML | L | XL |
|--------------------------|-------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 425 | 445 | 470 | 500 | 530 | 560 |
| Seat Tube Angle | 74,5° | 74,0° | 73,5° | 73,0° | 73,0° | 72,5° |
| Top Tube Length (mm) | 520 | 535 | 550 | 565 | 580 | 600 |
| Head Tube Length (mm) | 120 | 130 | 145 | 165 | 185 | 200 |
| Head Tube Angle | 71,0° | 72,3° | 73,0° | 73,0° | 73,0° | 73,0° |
| Fork Rake (mm) | 45 | 45 | 45 | 45 | 45 | 45 |
| Trail (mm) | 72,1 | 64 | 59,2 | 59,2 | 59,2 | 59,2 |
| Wheelbase (mm) | 976 | 977 | 980 | 991 | 1006 | 1020 |
| Chain Stay Length (mm) | 405 | 405 | 405 | 405 | 405 | 405 |
| Bottom Bracket Drop (mm) | 72 | 70 | 70 | 67 | 67 | 67 |
| Stack (mm) | 517 | 528 | 545 | 562 | 581 | 596 |
| Reach (mm) | 376 | 383 | 388 | 393 | 402 | 412 |
| Stand Over Height (mm) | 719 | 734 | 752 | 768 | 786 | 803 |
| Handlebar Width (mm) | 420 | 420 | 440 | 440 | 440 | 440 |
| Stem Length (mm) | 80 | 90 | 100 | 110 | 110 | 120 |
| Crank Length (mm) | 165 | 165 | 170 | 170 | 172,5 | 172,5 |

Alle spesifikasjonene kan endres uten varsel.