TCR ADVANCED PRO 1-DI2



SPECIFIKACIJE

OKVIR	
OKVIR	Advanced-Grade Composite, 12x142mm thru-axle, Disc
VILICE	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
KOMPONENTE	
KRMILO	Giant Contact SL
GRIPS	Stratus Lite 2.0 w/ gel
OPORA KRMILA	Giant Contact SL Aerolight, -10 degree
OPORA SEDEŽA	Giant Variant, Composite Offset -5/+15mm
SEDEŽ	Giant Fleet SL 7mm SST Rail With Giant ParticleFlow technology
PEDALA	GCS,GTS:Platform Pedal Rest GSC : no pedal
HEADSET	HS-GT-01
POGON	
PRESTAVNE ROČICE	Shimano 105 Di2 HRD
PREDNJI MENJALNIK	Shimano 105 Di2
ZADNJI MENJALNIK	Shimano 105 Di2
ZAVORE	Shimano 105 Di2 HRD
ZAVORNE ROČICE	Shimano 105 Di2 HRD
VERIŽNIK	Shimano 105 Di2, 11x34, 12-speed
VERIGA	KMC X12L-1
GONILKE Z VERIŽNIKI	Shimano 105 Di2, FC-R7100, 36/52 with Giant Power Pro power meter
BOTTOM BRACKET	Shimano, PressFit

OBROČNIKI	
OBROČI	Giant SLR 1 40 Carbon Disc Wheel System with Giant patented DBL (Dynamic Balanced Lacing) technology
PESTA	Giant SLR 1 40 Carbon Disc Wheel System with Giant patented DBL (Dynamic Balanced Lacing) technology
NAPERE	Giant SLR 1 40 Carbon Disc Wheel System with Giant patented DBL (Dynamic Balanced Lacing) technology
PLAŠČI	Giant Gavia COURSE 0 Tubeless, 700x30C, 170 TPI, Folding
DODATKI	Computer mount, tubeless prepared
LIMITS	
MAX TIRE CLEARANCE	700x33mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Višina glave okvirja (mm)	120	130	145	165	185	200
Krmilni kot	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Medosna razdalja (mm)	976	977	980	991	1006	1020
Dolžina cevi ob verigi (mm)	405	405	405	405	405	405
Oddaljenost zgornje cevi od gonilne osi (mm)	517	528	545	562	581	596
Doseg (mm)	376	383	388	393	402	412
Višina zgornje cevi (mm)	719	734	752	768	786	803
Dolžina gonilke (mm)	165	165	170	170	172,5	172,5

Vse navedene specifikacije se lahko spremenijo brez obvestila.