TCR ADVANCED PRO DISC 0 DI2

SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Cold Night/Chrome
FRAME	Advanced-Grade Composite, disc
FORK	Advanced-Grade Composite, full-composite OverDrive 2 steerer, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SLR XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Stratus Lite 2.0
STEM	Giant Contact SL XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SEATPOST	Giant Variant, composite, -5/+15mm offset
SADDLE	Giant Fleet SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Ultegra Di2 ST-R8170
FRONT DERAILLEUR	Shimano Ultegra Di2 FD-R8150
REAR DERAILLEUR	Shimano Ultegra Di2 RD-R8150
BRAKES	Shimano Ultegra Di2 hydraulic, Shimano RT-MT800 rotors [F]160mm, [R]140mm
BRAKE LEVERS	Shimano Ultegra Di2 hydraulic
CASSETTE	Shimano Ultegra, 12-speed, 11x34
CHAIN	Shimano Ultegra
CRANKSET	Shimano Ultegra, 36/52 with Giant Power Pro power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175m
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant SLR 1 36 Carbon Disc WheelSystem, [F] 36mm, [R] 36mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TIRES	CADEX Race, tubeless, 700x25c (26.5mm), folding
EXTRAS	computer mount, tubeless prepared, 32mm max tire size

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	425	445	470	500	530	560
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72,1	64	59,2	59,2	59,2	59,2
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	706	725	747	773	800	816
Handlebar Width (mm)	400	400	420	420	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	170	170	172,5	172,5	175	175
Wheel Size	700C	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.