

TCR ADVANCED PRO (DURA-ACE)



SPECIFIKATIONER

RAMME	
STØRRELSER	XS, S, M, M/L, L, XL
FARVER	Cryo Silver
RAMME	Advanced-grade composite, 12x142mm thru-axle, disc
FORGAFFEL	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYR	Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
GREB / STYRBÅND	Stratus Lite 2.0
FREMPIND	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SADELPIND	Giant Variant, composite, -5/+15mm offset
SADEL	Giant Fleet SL
PEDALER	platform pedal [GCS,GTS] N/A [all other GSC]
GEARGRUPPE	
SKIFTEGREB	Shimano Dura-Ace Di2
FORSKIFTER	Shimano Dura-Ace Di2 FD-R9250
BAGSKIFTER	Shimano Dura-Ace Di2 RD-R9250
BREMSE	Shimano Dura-Ace hydraulic, Shimano RT-CL900 rotors [F]160mm, [R]140mm
BREMSEGREB	Shimano Dura-Ace Di2
KASSETTE	Shimano Dura-Ace, 12-speed, 11x30
KÆDE	Shimano CN-M9100
KRANKSÆT	Shimano Dura-Ace, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
KRANKBOKS	Shimano, press fit

HJUL	
FÆLGE	Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
EGER	Giant Aero Carbon Spoke
DÆK	CADEX Road Race GC, tubeless, 700x30mm, folding
EKSTRA	computer mount, tubeless prepared, 33mm max tire size

Pris: 63.529,00 kr.

GEOMETRI

RAMME	S	M	ML	L	XL
Sadelrørslængde (mm)	445	470	500	530	560
Sadelrørvinkel	74,0°	73,5°	73,0°	73,0°	72,5°
Overrørslængde (mm)	535	550	565	580	600
Kronrørslængde (mm)	130	145	165	185	200
Kronrørvinkel	72,3°	73,0°	73,0°	73,0°	73,0°
Forgaffel fremspring (rake) (mm)	45	45	45	45	45
Sti (mm)	64	59,2	59,2	59,2	59,2
Akselafstand (mm)	977	980	991	1006	1020
Kædestagslængde (mm)	405	405	405	405	405
Krankboks drop (mm)	70	70	67	67	67
Stack (mm)	528	545	562	581	596
Reach (mm)	383	388	393	402	412
Skridthøjde (mm)	734	752	768	786	803
Styrbredde (mm)	420	440	440	440	440
Frempindslængde (mm)	90	100	110	110	120
Pedalarmslængde (mm)	165	170	170	172,5	172,5

Alle de anførte specifikationer kan ændres uden varsel.