

TCR ADVANCED PRO (DURA-ACE)

GIANT



SPECS

RAMME	
STØRRELSE	XS, S, M, M/L, L, XL
FARGE	Black/Rosso Corsa
RAMME	Advanced-grade Composite, 12x142mm thru-axle, disc
GAFFEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
DEMPER	N/A
KOMPONENTER	
STYRE	Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
GRIPS	Stratus Lite 2.0
STYRSTEM	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SETEPINNE	Giant Variant, composite, -5/+15mm offset
SADEL	Giant Fleet SL
PEDALER	platform pedal [GCS,GTS], N/A [all other GSC]
DRIVVERK	
GIRHENDLER	Shimano Dura-Ace Di2
FRONTGIR	Shimano Dura-Ace Di2 FD-R9250
BAKGIR	Shimano Dura-Ace Di2 RD-R9250
BREMSER	Shimano Dura-Ace Di2 hydraulic, Shimano RT-CL900 rotors [F]160mm, [R]140mm
BREMSEHENDLER	Shimano Dura-Ace Di2
KASSETT	Shimano Dura-Ace, 12-speed, 11x30
KJEDE	Shimano CN-M9100
KRANK	Shimano Dura-Ace, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

HJUL	
FELG	Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
EIKE	Giant Aero Carbon Spoke
DEKK	CADEX Road Race GC, tubeless, 700x30mm, folding
EXTRAS	computer mount, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRI

RAMME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	425	445	470	500	530	560
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72,1	64	59,2	59,2	59,2	59,2
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	719	734	752	768	786	803
Handlebar Width (mm)	420	420	440	440	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172,5	172,5

Alle spesifikasjonene kan endres uten varsel.