

TCR ADVANCED PRO (DURA-ACE)

GIANT



SPECIFIKACIJE

| OKVIR               |                                                                                                    |
|---------------------|----------------------------------------------------------------------------------------------------|
| VELIKOSTI           | XS, S, M, M/L, L, XL                                                                               |
| BARVE               | Cryo Silver                                                                                        |
| OKVIR               | Advanced-grade composite, 12x142mm thru-axle, disc                                                 |
| VILICE              | Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc       |
| KOMPONENTE          |                                                                                                    |
| KRMILO              | Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm |
| GRIPS               | Stratus Lite 2.0                                                                                   |
| OPORA KRMILA        | Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm                  |
| OPORA SEDEŽA        | Giant Variant, composite, -5/+15mm offset                                                          |
| SEDEŽ               | Giant Fleet SL                                                                                     |
| PEDALA              | platform pedal [GCS,GTS] N/A [all other GSC]                                                       |
| POGON               |                                                                                                    |
| PRESTAVNE ROČICE    | Shimano Dura-Ace Di2                                                                               |
| PREDNJI MENJALNIK   | Shimano Dura-Ace Di2 FD-R9250                                                                      |
| ZADNJI MENJALNIK    | Shimano Dura-Ace Di2 RD-R9250                                                                      |
| ZAVORE              | Shimano Dura-Ace hydraulic, Shimano RT-CL900 rotors [F]160mm, [R]140mm                             |
| ZAVORNE ROČICE      | Shimano Dura-Ace Di2                                                                               |
| VERIŽNIK            | Shimano Dura-Ace, 12-speed, 11x30                                                                  |
| VERIGA              | Shimano CN-M9100                                                                                   |
| GONILKE Z VERIŽNIKI | Shimano Dura-Ace, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm               |
| BOTTOM BRACKET      | Shimano, press fit                                                                                 |

| OBROČNIKI |                                                                                                                                   |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------|
| OBROČI    | Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm                                                                                      |
| PESTA     | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle |
| NAPERE    | Giant Aero Carbon Spoke                                                                                                           |
| PLAŠČI    | CADEX Road Race GC, tubeless, 700x30mm, folding                                                                                   |
| DODATKI   | computer mount, tubeless prepared, 33mm max tire size                                                                             |

GEOMETRIJA

| OKVIR                                        | XS    | S     | M     | ML    | L     | XL    |
|----------------------------------------------|-------|-------|-------|-------|-------|-------|
| Dolžina sedežne cevi (mm)                    | 425   | 445   | 470   | 500   | 530   | 560   |
| Kot sedežne cevi                             | 74,5° | 74,0° | 73,5° | 73,0° | 73,0° | 72,5° |
| Top Tube Length (mm)                         | 520   | 535   | 550   | 565   | 580   | 600   |
| Višina glave okvirja (mm)                    | 120   | 130   | 145   | 165   | 185   | 200   |
| Krmilni kot                                  | 71,0° | 72,3° | 73,0° | 73,0° | 73,0° | 73,0° |
| Zamik vpetja osi (mm)                        | 45    | 45    | 45    | 45    | 45    | 45    |
| Trail (mm)                                   | 72,1  | 64    | 59,2  | 59,2  | 59,2  | 59,2  |
| Medosna razdalja (mm)                        | 976   | 977   | 980   | 991   | 1006  | 1020  |
| Dolžina cevi ob verigi (mm)                  | 405   | 405   | 405   | 405   | 405   | 405   |
| Bottom Bracket Drop (mm)                     | 72    | 70    | 70    | 67    | 67    | 67    |
| Oddaljenost zgornje cevi od gonilne osi (mm) | 517   | 528   | 545   | 562   | 581   | 596   |
| Doseg (mm)                                   | 376   | 383   | 388   | 393   | 402   | 412   |
| Višina zgornje cevi (mm)                     | 719   | 734   | 752   | 768   | 786   | 803   |
| Širina krmila (mm)                           | 420   | 420   | 440   | 440   | 440   | 440   |
| Dolžina opore krmila (mm)                    | 80    | 90    | 100   | 110   | 110   | 120   |
| Dolžina gonilke (mm)                         | 165   | 165   | 170   | 170   | 172,5 | 172,5 |

Vse navedene specifikacije se lahko spremenijo brez obvestila.