

# TCR ADVANCED PRO (DURA-ACE)

GIANT



## SPECS

RAM	
STORLEKAR	XS, S, M, M/L, L, XL
FÄRGER	Black/Rosso Corsa
RAM	Advanced-grade Composite, 12x142mm thru-axle, disc
GAFFEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
BAKDÄMPARE	N/A
KOMPONENTER	
STYRE	Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
GREPPAR	Stratus Lite 2.0
STAM	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SADELSTOLPE	Giant Variant, composite, -5/+15mm offset
SADEL	Giant Fleet SL
PEDALER	platform pedal [GCS,GTS], N/A [all other GSC]
DRIVLINA	
VÄXLAR	Shimano Dura-Ace Di2
FRAMVÄXEL	Shimano Dura-Ace Di2 FD-R9250
BAKVÄXEL	Shimano Dura-Ace Di2 RD-R9250
BROMSAR	Shimano Dura-Ace Di2 hydraulic, Shimano RT-CL900 rotors [F]160mm, [R]140mm
BROMSSPAKAR	Shimano Dura-Ace Di2
KASSETT	Shimano Dura-Ace, 12-speed, 11x30
KEDJA	Shimano CN-M9100
VEVPARTI	Shimano Dura-Ace, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BROMSREGLAGE	Shimano, press fit

HJUL	
FÄLGAR	Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
EKRAR	Giant Aero Carbon Spoke
DÄCK	CADEX Road Race GC, tubeless, 700x30mm, folding
EXTRAFUNKTIONER	computer mount, tubeless prepared, 33mm max tire size
GRÄNSER	
MAX DÄCKAVSTÅND	33mm

Price: 96 990,00 kr

## GEOMETRY

RAM	S	M	ML	L	XL
Längd sadelrör (mm)	445	470	500	530	560
Vinkel sadelrör	74,0°	73,5°	73,0°	73,0°	72,5°
Topprörets längd (mm)	535	550	565	580	600
Styrhuvud Längd (mm)	130	145	165	185	200
Vinkel styrhuvud	72,3°	73,0°	73,0°	73,0°	73,0°
Gaffelvinkel (mm)	45	45	45	45	45
Spår (mm)	64	59,2	59,2	59,2	59,2
Hjulbas (mm)	977	980	991	1006	1020
Kedjestagslängd (mm)	405	405	405	405	405
Nedre fäste Drop (mm)	70	70	67	67	67
Stack (mm)	528	545	562	581	596
Reach (mm)	383	388	393	402	412
Stå över höjden (mm)	734	752	768	786	803
Styrets bredd (mm)	420	440	440	440	440
Stamlängd (mm)	90	100	110	110	120
Vevlängd (mm)	165	170	170	172,5	172,5

All specifications listed are subject to change without notice.