

TCR ADVANCED PRO-FF



SPECS

TELAIO	
TAGLIE	XS, S, M, M/L, L, XL
COLORAZIONI	Obsidian Pulse, Supernova Grey
TELAIO	Advanced-grade Composite, 12x142mm thru-axle, disc
FORCELLA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTISTICA	
REGGISSELLA	Giant Variant, composite, -5/+15mm offset

RUOTE	
EXTRA	computer mount, tubeless prepared
LIMITI	
SEZIONE MASSIMA SUPPORTATA	33mm max tire size

Prezzo: 2.399,00 €

GEOMETRIA

TELAIO	XS	S	M	ML	L	XL
Lunghezza Tubo Sella (mm)	425	445	470	500	530	560
Angolo Tubo Sella	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Lunghezza Tubo Orizzontale (mm)	520	535	550	565	580	600
Lunghezza Tubo Sterzo (mm)	120	130	145	165	185	200
Angolo Sterzo	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Rake Forcella (mm)	45	45	45	45	45	45
Avancorsa (mm)	72,1	64	59,2	59,2	59,2	59,2
Interasse (mm)	976	977	980	991	1006	1020
Lunghezza Carro Posteriore (mm)	405	405	405	405	405	405
Drop Movimento Centrale (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Altezza stand over (mm)	719	734	752	768	786	803
Larghezza Manubrio c/c (mm)	420	420	440	440	440	440
Lunghezza Attacco Manubrio (mm)	80	90	100	110	110	120
Lunghezza Pedivella (mm)	165	165	170	170	172,5	172,5

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.