

TCR ADVANCED PRO FRAMESET



SPECS

FRAME	
SIZES	XS, S, M, ML, L, XL
COLOURS	Gloss Blue Dragonfly/Brushed Foil
FRAME	Advanced-Grade Composite 12x142mm thru-axle, Disc
FORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
COMPONENTS	
SEATPOST	Giant Variant, Composite Offset -5/+15mm
DRIVETRAIN	
SHIFTERS	Compatible with Shimano Di2, SRAM AXS/eTap, new Campagnolo Super Record and Shimano 9100, 8000, 7100, 7000 mechanical groupsets.
BOTTOM BRACKET	Pressfit 86.5x41mm. Not included

WHEELS	
EXTRAS	Headset, spacers, axles, out front computer mount
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	425	445	470	500	530	560
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71.0°	72.3°	73.5°	73.0°	73.0°	72.5°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72	64	59	59	59	59
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	69.5	69.5	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	703	722	743	771	798	822
Handlebar Width (mm)	400	400	420	420	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	170	170	172.5	172.5	175	175
Wheel Size	700C	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.