

# TCR ADVANCED SL 0 DA

**GIANT**



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLORS</b>	Black Lava / Iris
<b>FRAME</b>	Advanced SL-Grade Composite, 12x142mm thru-axle, integrated seatpost, disc
<b>FORK</b>	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR XS:39/40cm, S:39/40cm, M:39/42cm, M/L:39/42cm, L:41/44cm, XL:41/44cm
<b>GRIPS</b>	Stratus Lite 2.0
<b>STEM</b>	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
<b>SEATPOST</b>	Giant Integrated Seatpost, -5/+15mm offset
<b>SADDLE</b>	CADEX AMP
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano Dura-Ace Di2
<b>FRONT DERAILLEUR</b>	Shimano Dura-Ace Di2 FD-R9250
<b>REAR DERAILLEUR</b>	Shimano Dura-Ace Di2 RD-R9250
<b>BRAKES</b>	Shimano Dura-Ace Di2 hydraulic, Shimano RT-CL900 rotors [F]160mm, [R]140mm
<b>BRAKE LEVERS</b>	Shimano Dura-Ace Di2
<b>CASSETTE</b>	Shimano Dura-Ace, 12-speed, 11x34
<b>CHAIN</b>	Shimano CN-M9100
<b>CRANKSET</b>	Shimano Dura-Ace, 36/52 with Shimano FC-9200P power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
<b>BOTTOM BRACKET</b>	Shimano, press fit

WHEELS	
<b>RIMS</b>	CADEX Max 40 WheelSystem, [F]40mm, [R]40mm
<b>HUBS</b>	[F] CADEX R3 Hub, CenterLock, 12mm thru-axle [R] CADEX R3-C48 Aero Hub, 48t ratchet driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	CADEX Aero Carbon Spoke
<b>TIRES</b>	CADEX Race GC, tubeless, 700x28c (28mm), folding
<b>EXTRAS</b>	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
LIMITS	
<b>MAX TIRE CLEARANCE</b>	33mm

## GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	680	710	740	770	800	830
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72	64	59	59	59	59
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	69,5	69,5	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	703	722	743	771	798	822
Handlebar Width (mm)	400	400	420	420	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	170	170	172,5	172,5	175	175
Wheel Size	700C	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.