

TCR ADVANCED SL 0-DA



SPECIFIKACIJE

OKVIR	
OKVIR	Advanced SL-Grade Composite, 12x142mm thru-axle, Integrated Seatpost, Disc
VILICE	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
KOMPONENTE	
KRMILO	CADEX Race One-Piece
GRIPS	Stratus Lite 2.0 w/ gel
OPORA KRMILA	CADEX Race One-Piece
OPORA SEDEŽA	Advanced SL-Grade Composite, Integrated Design Offset -5/+15mm
SEDEŽ	CADEX Amp With One-piece SMC Base / 9mm Carbon Rail / ParticleFlow technology
PEDALA	GCS,GTS:Platform Pedal Rest GSC : no pedal
HEADSET	HS-GT-01
POGON	
PRESTAVNE ROČICE	Shimano Dura Ace Di2
PREDNJI MENJALNIK	Shimano Dura Ace Di2
ZADNJI MENJALNIK	Shimano Dura Ace Di2
ZAVORE	Shimano Dura Ace HRD
ZAVORNE ROČICE	Shimano Dura Ace Di2 HRD
VERIŽNIK	Shimano Dura Ace, 11x34
VERIGA	Shimano CN-M9100, 12-speed
GONILKE Z VERIŽNIKI	Shimano Dura Ace, 36/52
BOTTOM BRACKET	Cema Ceramic PF

OBROČNIKI	
OBROČI	CADEX 40 Max Disc Wheel System Hookless + Carbon spoke with Giant patented DBL (Dynamic Balanced Lacing) technology
PESTA	CADEX 40 Max Disc Wheel System Hookless + Carbon spoke with Giant patented DBL (Dynamic Balanced Lacing) technology
NAPERE	CADEX 40 Max Disc Wheel System Hookless + Carbon spoke with Giant patented DBL (Dynamic Balanced Lacing) technology
PLAŠČI	CADEX Road Race GC Tubeless 700x30mm 240 TPI, Folding
DODATKI	Computer mount, tubeless prepared
LIMITS	
MAX TIRE CLEARANCE	700x33mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Višina glave okvirja (mm)	120	130	145	165	185	200
Krmilni kot	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Medosna razdalja (mm)	976	977	980	991	1006	1020
Dolžina cevi ob verigi (mm)	405	405	405	405	405	405
Oddaljenost zgornje cevi od gonilne osi (mm)	517	528	545	562	581	596
Doseg (mm)	376	383	388	393	402	412
Višina zgornje cevi (mm)	719	734	752	768	786	803
Dolžina gonilke (mm)	165	165	170	170	172,5	172,5

Vse navedene specifikacije se lahko spremenijo brez obvestila.