

TCR ADVANCED SL 0 DURA-ACE

GIANT



TECHNIQUES

CADRE	
TAILLES	XS, S, M, M/L, L, XL
COLORIS	Mariana Blue/Iris
CADRE	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
FOURCHE	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
POIGNÉES	Stratus Lite 2.0
POTENCE	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
TIGE DE SELLE	Giant Integrated Seatpost, -5/+15mm offset
SELLE	CADEX AMP
DÉRAILLEUR	
MANETTES	Shimano Dura-Ace Di2
DÉRAILLEUR AVANT	Shimano Dura-Ace Di2 FD-R9250
DÉRAILLEUR ARRIÈRE	Shimano Dura-Ace Di2 RD-R9250
FREINS	Shimano Dura-Ace Di2 hydraulic, Shimano RT-CL900 rotors [F]160mm, [R]140mm
LEVIERS DE FREIN	Shimano Dura-Ace Di2
CASSETTE	Shimano Dura-Ace, 12-speed, 11x34
CHAÎNE	Shimano CN-M9100
PÉDALIER	Shimano Dura-Ace, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOITIER DE PÉDALIER	CEMA ceramic, press fit

ROUES	
JANTES	CADEX Max 40 WheelSystem, [F]40mm, [R]40mm
MOYEUX	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C48 Aero Hub, 48t ratchet driver, CenterLock, 12mm thru-axle
RAYONS	CADEX Aero Carbon Spoke
PNEUS	CADEX Race GC, tubeless, 700x30mm, folding
EXTRAS	computer mount, tubeless prepared, 33mm max tire size
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
LIMITES	
DÉGAGEMENT MAX DES PNEUS	33mm

Prix Public Conseillé: 11 500,00 €

GÉOMÉTRIE

CADRE	XS	S	M	ML	L	XL
Longueur de tube de selle (mm)	680	710	740	770	800	830
Angle de tube de selle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Longueur du tube supérieur (mm)	520	535	550	565	580	600
Longueur du tube de direction (mm)	120	130	145	165	185	200
Angle du tube de direction	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Déport de fourche (mm)	45	45	45	45	45	45
Trail (mm)	72,1	64	59,2	59,2	59,2	59,2
Empattement (mm)	976	977	980	991	1006	1020
Longueur des bases (mm)	405	405	405	405	405	405
Drop du boîtier de pédalier (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Hauteur en statique (mm)	719	734	752	768	786	803
Largeur de cintre (mm)	420	420	440	440	440	440
Longueur de potence (mm)	80	90	100	110	110	120
Longueur des manivelles (mm)	165	165	170	170	172,5	172,5

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.