

# TCR ADVANCED SL 0 (RED)

**GIANT**



## SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Turbo Teal
FRAME	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
FORK	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
GRIPS	Stratus Lite 2.0
STEM	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SEATPOST	Giant Integrated Seatpost, -5/+15mm offset
SADDLE	CADEX AMP
DRIVETRAIN	
SHIFTERS	SRAM RED AXS E1
FRONT DERAILLEUR	SRAM RED AXS E1
REAR DERAILLEUR	SRAM RED AXS E1
BRAKES	SRAM RED E1 hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM RED AXS E1
CASSETTE	SRAM RED, 12-speed, 10x33
CHAIN	SRAM RED E1, 12-speed
CRANKSET	SRAM RED E1 DUB, 35/48 with integrated Quarq Power Meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB ceramic, press fit

WHEELS	
RIMS	CADEX Max 40 WheelSystem, [F]40mm, [R]40mm
HUBS	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C48 Aero Hub, 48t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	CADEX Aero Carbon Spoke
TIRES	CADEX Road Race GC, tubeless, 700x30mm, folding
EXTRAS	computer mount, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

**Suggested Retail Price (CDN): \$15,899.00**

## FRAME GEOMETRY

FRAME	XS	S	M	ML	L
Seat Tube Length (mm)	680	710	740	770	800
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°
Top Tube Length (mm)	520	535	550	565	580
Head Tube Length (mm)	120	130	145	165	185
Head Tube Angle	71.0°	72.3°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45
Trail (mm)	72.1	64	59.2	59.2	59.2
Wheelbase (mm)	976	977	980	991	1006
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67
Stack (mm)	517	528	545	562	581
Reach (mm)	376	383	388	393	402
Stand Over Height (mm)	719	734	752	768	786
Handlebar Width (mm)	420	420	440	440	440
Stem Length (mm)	80	90	100	110	110
Crank Length (mm)	165	165	170	170	172.5

All prices and specifications are subject to change without notice.