

TCR ADVANCED SL 0 RED



SPECS

FRAME	
SIZES	S, M, ML, L
COLOURS	Gloss Black Lava/Iris
FRAME	Advanced SL-Grade Composite, 12x142mm thru-axle, Integrated Seatpost, Disc
FORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SLR, 10.5 degree flare
GRIPS	Giant Stratus Lite 2.0 with gel
STEM	Giant Contact SLR Aerolight
SEATPOST	Advanced SL-Grade Composite, Integrated Design, ISP Clamps: Standard (25mm) and Long version (45mm) Offset -5/+15mm
SADDLE	CADEX Amp With One-piece SMC Base / 9mm Carbon Rail / ParticleFlow technology
PEDALS	PEDALS NOT SUPPLIED
DRIVETRAIN	
SHIFTERS	New SRAM Red AXS 2x12
FRONT DERAILLEUR	New SRAM Red AXS
REAR DERAILLEUR	New SRAM Red AXS
BRAKES	New SRAM Red AXS HRD, PaceLine 160/140mm rotors
BRAKE LEVERS	New SRAM Red AXS HRD
CASSETTE	New SRAM Red XG-1290, 10x33
CHAIN	New SRAM Red
CRANKSET	New SRAM Red DUB 35/48 with Quarq power meter
BOTTOM BRACKET	SRAM DUB, Press Fit

WHEELS	
RIMS	New CADEX 40 Max Disc Wheel System Hookless + Carbon spoke with GIANT patented DBL (Dynamic Balanced Lacing) technology
HUBS	[F] CADEX R3 Hub, CenterLock, 12mm thru-axle [R] CADEX R3-C48 Aero Hub, 48t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	CADEX Aero Carbon Spoke
TYRES	New CADEX Race GC Tubeless 700x28mm effective 170 TPI, Folding
EXTRAS	Factory tubeless set up, out front computer mount
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	680	710	740	770	800	830
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72	64	59	59	59	59
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	69.5	69.5	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	703	722	743	771	798	822
Handlebar Width (mm)	400	400	420	420	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	170	170	172.5	172.5	175	175
Wheel Size	700C	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.