

TCR ADVANCED SL 0 RED

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Black Lava
CUADRO	Advanced SL-Grade Composite, 12x142mm thru-axle, integrated seatpost, disc
TIJERA	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant Contact SLR XS:37/40cm, S:37/40cm, M:39/42cm, M/L:39/42cm, L:41/44cm, XL:41/44cm
GRIPS	Stratus Lite 2.0
POTENCIA	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
POSTE DE ASIENTO	Giant Integrated Seatpost, -5/+15mm offset
ASIENTO	CADEX AMP
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM RED AXS HRD, ED-RED-E1
DESVIADOR	SRAM RED AXS FD-RED-E-E1
CAMBIO TRASERO	SRAM RED AXS RD-RED-E-E1
FRENOS	SRAM RED hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
PALANCAS DE FRENOS	SRAM RED AXS HRD, ED-RED-E1
CASSETTE	SRAM RED, 12-speed, 10x33
CADENA	SRAM RED CN-RED-E1
MULTIPLICACIÓN	SRAM RED PM E1 DUB, 35/48 with power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
EJE DE CENTRO	SRAM, press fit

RUEDAS	
RUEDAS	CADEX Max 40 WheelSystem, [F]40mm, [R]40mm
MAZAS	[F] CADEX R3 Hub, CenterLock, 12mm thru-axle [R] CADEX R3-C48 Aero Hub, 48t ratchet driver, CenterLock, 12mm thru-axle
RAYOS	CADEX Aero Carbon Spoke
NEUMÁTICOS	CADEX Race GC, tubeless, 700x28c (28mm), folding
EXTRAS	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

Precio: \$242,990.00

GEOMETRÍA

CUADRO	XS	S	M	ML	L
Longitud de la Base del Poste de Asiento (mm)	680	710	740	770	800
Ángulo de la Base del Poste de Asiento	74.5°	74.0°	73.5°	73.0°	73.0°
Longitud del Tubo Superior (mm)	520	535	550	565	580
Longitud del Telescopio (mm)	120	130	145	165	185
Ángulo del Telescopio	71.0°	72.3°	73.0°	73.0°	73.0°
Rake (mm)	45	45	45	45	45
Trail (mm)	72	64	59	59	59
Distancia entre Ejes (mm)	976	977	980	991	1006
Longitud de Vaina Inferior (mm)	405	405	405	405	405
Caída del Eje de Centro (mm)	72	69.5	69.5	67	67
Stack (mm)	517	528	545	562	581
Reach (mm)	376	383	388	393	402
Altura del Tubo Superior al Suelo (mm)	703	722	743	771	798
Ancho del Manubrio (mm)	400	400	420	420	440
Longitud de la Potencia (mm)	80	90	100	110	110
Longitud de la Biela (mm)	170	170	172.5	172.5	175
Tamaño de las Ruedas	700C	700C	700C	700C	700C

Todas las especificaciones están sujetas a cambios sin previo aviso.