

TCR ADVANCED SL 0 (RED)

GIANT



TEKNISET TIEDOT

RUNKO	
KOOT	S, M, M/L, L, XL
VÄRIT	Turbo Teal
RUNKO	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
HAARUKKA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
ISKUNVAIMENNIN	N/A
KOMPONENTIT	
OHJAUSTANKO	Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
GRIPIT	Stratus Lite 2.0
OHJAINKANNATIN	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SATULATOLPPA	Giant Integrated Seatpost, -5/+15mm offset
SATULA	CADEX AMP
VOIMANSIIRTO	
VAIHDEVIPU	SRAM RED AXS E1
ETUVAIHTAJA	SRAM RED AXS E1
TAKAVAIHTAJA	SRAM RED AXS E1
JARRUT	SRAM RED E1 hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
JARRUKAHVAT	SRAM RED AXS E1
RATASPAKKA	SRAM RED, 12-speed, 10x33
KETJUT	SRAM RED E1, 12-speed
KAMPISARJA	SRAM RED E1 DUB, 35/48 with integrated Quarq Power Meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
KESKIÖ	SRAM DUB ceramic, press fit

RENKAAT	
VANTEET	CADEX Max 40 WheelSystem, [F]40mm, [R]40mm
NAVAT	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C48 Aero Hub, 48t ratchet driver, CenterLock, 12mm thru-axle
PINNAT	CADEX Aero Carbon Spoke
RENKAAT	CADEX Road Race GC, tubeless, 700x30mm, folding
LISÄTIEDOT	computer mount, tubeless prepared, 33mm max tire size
RAJOITTEET	
MAX RENGASVARA	33mm

Suositusuhinta: 13 299,00 €

GEOMETRIA

RUNKO	S	M	ML	L	XL
Satulaputken pituus (mm)	710	740	770	800	830
Satulaputken kulma	74,0°	73,5°	73,0°	73,0°	72,5°
Vaakaputken pituus (mm)	535	550	565	580	600
Emäputken pituus (mm)	130	145	165	185	200
Emäputken kulma	72,3°	73,0°	73,0°	73,0°	73,0°
Haarukan offset (mm)	45	45	45	45	45
Trail-mitta (mm)	64	59,2	59,2	59,2	59,2
Akseliväli (mm)	977	980	991	1006	1020
Takahaarukan alaputken pituus (mm)	405	405	405	405	405
Keskion pudotus (mm)	70	70	67	67	67
Stack-mitta (mm)	528	545	562	581	596
Reach-mitta (mm)	383	388	393	402	412
Standover-mitta (mm)	734	752	768	786	803
Ohjaustangon leveys (mm)	420	440	440	440	440
Ohjainkannattimen pituus (mm)	90	100	110	110	120
Kammen pituus (mm)	165	170	170	172,5	172,5

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.