

TCR ADVANCED SL 0 RED

GIANT



TECHNIQUES

CADRE	
TAILLES	XS, S, M, ML, L, XL
COLORIS	Prism Pearl
CADRE	Advanced SL-Grade Composite, 12x142mm thru-axle, Integrated Seatpost, Disc
FOURCHE	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
COMPOSANTS	
CINTRE	Cadex Race One-Piece, 31.8, Drop: 125mm (120mm for 360 / 380mm bar) Reach: 72mm (68mm for 360 / 380mm bar), XS/S : 420/370; M/ML/L/XL : 440/390
POIGNÉES	Stratus Lite 2.0 w/ gel
POTENCE	Cadex Race One-Piece, XS/S : 90; M/ML/L : 110; XL : 120
TIGE DE SELLE	Advanced SL-Grade Composite, Integrated Design Offset -5/+15mm
SELLE	Cadex Amp With One-piece SMC Base / 9mm Carbon Rail / ParticleFlow technology
JEU DE DIRECTION	Advanced SL-Grade Composite, Integrated Design Offset -5/+15mm
DÉRAILLEUR	
MANETTES	Sram Red AXS HRD, ED-RED-E1
DÉRAILLEUR AVANT	Sram Red AXS, FD-RED-E-E1
DÉRAILLEUR ARRIÈRE	Sram Red AXS, RD-RED-E-E1
FREINS	Sram Red AXS HRD, ED-RED-E1, Sram PaceLine X, [F]160[R]140
LEVIER DE FREIN	Sram Red AXS HRD, ED-RED-E1
CASSETTE	Sram Red XG-1290, 12-speed, 10-33
CHAÎNE	Sram CN-RED-E1, 12-speed
PÉDALIER	Sram FC RED PM E1, DUB, 35/48 with Power Meter
BOITIER DE PÉDALIER	SRAM DUB Ceramic, Press Fit

ROUES	
JANTES	Cadex 40 Max Disc Wheel System Hookless + Carbon spoke with GIANT patented DBL (Dynamic Balanced Lacing) technology
PNEUS	Cadex Road Race GC Tubeless 700x30mm 240 TPI, Folding
EXTRAS	Computer mount, tubeless prepared
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
LIMITES	
DÉGAGEMENT MAX DES PNEUS	700x33mm

Prix Public Conseillé: 11 800,00 €

GÉOMÉTRIE

CADRE	XS	S	M	ML	L	XL
Longueur de tube de selle (mm)	680	710	740	770	800	830
Angle de tube de selle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Longueur du tube supérieur (mm)	520	535	550	565	580	600
Longueur du tube de direction (mm)	120	130	145	165	185	200
Angle du tube de direction	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Déport de fourche (mm)	45	45	45	45	45	45
Trail (mm)	72,1	64	59,2	59,2	59,2	59,2
Empattement (mm)	976	977	980	991	1006	1020
Longueur des bases (mm)	405	405	405	405	405	405
Drop du boîtier de pédalier (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Hauteur en statique (mm)	719	734	752	768	786	803
Largeur de cintre (mm)	420	420	440	440	440	440
Longueur de potence (mm)	80	90	100	110	110	120
Longueur des manivelles (mm)	165	165	170	170	172,5	172,5

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.