

TCR ADVANCED SL 0 (RED)

GIANT



SPECIFICATIES

FRAME	
MATEN	S, M, M/L, L, XL
KLEUREN	Turbo Teal
FRAME	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
VOORVORK	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
HANDVATTEN	Stratus Lite 2.0
STUURPEN	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
ZADELLEN	Giant Integrated Seatpost, -5/+15mm offset
ZADEL	CADEX AMP
AFMONTAGE	
SHIFTERS	SRAM RED AXS E1
VOORDERAILLEUR	SRAM RED AXS E1
ACHTERDERAILLEUR	SRAM RED AXS E1
REMMEN	SRAM RED E1 hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
REMHENDELS	SRAM RED AXS E1
CASSETTE	SRAM RED, 12-speed, 10x33
AANDRIJVING	SRAM RED E1, 12-speed
CRANKSET	SRAM RED E1 DUB, 35/48 with integrated Quarq Power Meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB ceramic, press fit

WIELSET	
VELGEN	CADEX Max 40 WheelSystem, [F]40mm, [R]40mm
NAVEN	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C48 Aero Hub, 48t ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	CADEX Aero Carbon Spoke
BANDEN	CADEX Road Race GC, tubeless, 700x30mm, folding
EXTRA'S	computer mount, tubeless prepared, 33mm max tire size
LIMITS	
MAXIMALE BANDENVRIJHEID	33mm

Adviesprijs: € 12.499,00

GEOMETRIE

FRAME	S	M	ML	L	XL
Zitbuis Lengte (mm)	710	740	770	800	830
Zitbuis Hoek	74,0°	73,5°	73,0°	73,0°	72,5°
Frame Lengte (horizontaal) (mm)	535	550	565	580	600
Balhoofdbuis Lengte (mm)	130	145	165	185	200
Balhoofdbuis Hoek	72,3°	73,0°	73,0°	73,0°	73,0°
Vork Sprong (mm)	45	45	45	45	45
Naloop (mm)	64	59,2	59,2	59,2	59,2
Wielbasis (mm)	977	980	991	1006	1020
Liggende achtervork lengte (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	70	70	67	67	67
Stack (mm)	528	545	562	581	596
Reach (mm)	383	388	393	402	412
Stand Over Height (mm)	734	752	768	786	803
Stuur breedte (mm)	420	440	440	440	440
Stuurpen Lengte (mm)	90	100	110	110	120
Cranklengte (mm)	165	170	170	172,5	172,5

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.