TCR ADVANCED SL 0-RED



SPECS

QUADRO	
TAMANHOS	XS, S, M, M/L, L, XL
CORES	Prism Pearl/Iris
QUADRO	Advanced SL-grade composite, 12x142mm thru-axle, integrated seatpost, disc
FORQUILHA	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTES	
GUIADOR	CADEX Race Integrated XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
PUNHOS	Stratus Lite 2.0
AVANÇO	CADEX Race Integrated XS:90mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
ESPIGÃO DE SELIM	Giant Integrated Seatpost, -5/+15mm offset
SELIM	CADEX AMP
TRANSMISSÃO	
MANETES	SRAM RED AXS E1
DESVIADOR DIANTEIRO	SRAM RED AXS E1
DESVIADOR TRASEIRO	SRAM RED AXS E1
TRAVÕES	SRAM RED E1 hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
MANÍPULOS DOS TRAVÕES	SRAM RED AXS E1
CASSETE	SRAM RED, 12-speed, 10x33
CORRENTE	SRAM RED E1, 12-speed
CONJUNTO PEDALEIRO	SRAM RED E1 DUB, 35/48 with integrated Quarq Power Meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
MOVIMENTO CENTRAL	SRAM DUB ceramic, press fit

RODAS	
AROS	CADEX Max 40 WheelSystem, [F]40mm, [R]40mm
CUBOS	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle [R] CADEX R3-C48 Aero Hub, 48t ratchet driver, CenterLock, 12mm thru-axle
RAIOS	CADEX Aero Carbon Spoke
PNEUS	CADEX Road Race GC, tubeless, 700x30mm, folding
EXTRAS	computer mount, tubeless prepared, 33mm max tire size
LIMITES	
FOLGA MÁXIMA DO PNEU	33mm

Preço: 10 399,00 €

GEOMETRIA

QUADRO	XS	S	M	ML	L	XL
Comprimento do tubo do assento (mm)	680	710	740	770	800	830
Ângulo do tubo do assento	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Comprimento do tubo superior (mm)	520	535	550	565	580	600
Comprimento do tubo principal (mm)	120	130	145	165	185	200
Ângulo do tubo principal	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Garfo ancinho (mm)	45	45	45	45	45	45
Trilha (mm)	72,1	64	59,2	59,2	59,2	59,2
distância entre eixos (mm)	976	977	980	991	1006	1020
Comprimento Chain Stay (mm)	405	405	405	405	405	405
Suporte inferior (mm)	72	70	70	67	67	67
Pilha (mm)	517	528	545	562	581	596
Alcançar (mm)	376	383	388	393	402	412
Altura do standover (mm)	719	734	752	768	786	803
Largura do guidão (mm)	420	420	440	440	440	440
Comprimento da haste (mm)	80	90	100	110	110	120
Comprimento da Manivela (mm)	165	165	170	170	172,5	172,5

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.