

TCR ADVANCED SL 0 (RED)

GIANT



SPECS

CADRU	
MARIMI	XS, S, M, M/L, L, XL
CULORI	Turbo Teal
CADRU	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
FURCA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
SOC	N/A
COMPONENTE	
GHIDON	Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
GRIPS	Stratus Lite 2.0
PIPA	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
TIJA SA	Giant Integrated Seatpost, -5/+15mm offset
SA	CADEX AMP
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	SRAM RED AXS E1
SCHIMBATOR FATA	SRAM RED AXS E1
SCHIMBATOR SPATE	SRAM RED AXS E1
FRANE	SRAM RED E1 hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
MANETE FRANA	SRAM RED AXS E1
PINIOANE	SRAM RED, 12-speed, 10x33
LANT	SRAM RED E1, 12-speed
ANGRENAJ	SRAM RED E1 DUB, 35/48 with integrated Quarq Power Meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB ceramic, press fit

ROTI	
JANTE	CADEX Max 40 WheelSystem, [F]40mm, [R]40mm
BUTUCI	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C48 Aero Hub, 48t ratchet driver, CenterLock, 12mm thru-axle
SPITE	CADEX Aero Carbon Spoke
ANVELOPE	CADEX Road Race GC, tubeless, 700x30mm, folding
EXTRAS	computer mount, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRIE

CADRU	XS	S	M	ML	L	XL
Seat Tube Length (mm)	680	710	740	770	800	830
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72,1	64	59,2	59,2	59,2	59,2
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	719	734	752	768	786	803
Handlebar Width (mm)	420	420	440	440	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172,5	172,5

Toate specificatiile enumerate se pot schimba fara notificare prealabila.