

TCR ADVANCED SL 0 (RED)

GIANT

SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Turbo Teal
OKVIR	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
VILICE	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
GRIPS	Stratus Lite 2.0
OPORA KRMILA	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
OPORA SEDEŽA	Giant Integrated Seatpost, -5/+15mm offset
SEDEŽ	CADEX AMP
POGON	
PRESTAVNE ROČICE	SRAM RED AXS E1
PREDNJI MENJALNIK	SRAM RED AXS E1
ZADNJI MENJALNIK	SRAM RED AXS E1
ZAVORE	SRAM RED E1 hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
ZAVORNE ROČICE	SRAM RED AXS E1
VERIŽNIK	SRAM RED, 12-speed, 10x33
VERIGA	SRAM RED E1, 12-speed
GONILKE Z VERIŽNIKI	SRAM RED E1 DUB, 35/48 with integrated Quarq Power Meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB ceramic, press fit

OBROČNIKI	
OBROČI	CADEX Max 40 WheelSystem, [F]40mm, [R]40mm
PESTA	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C48 Aero Hub, 48t ratchet driver, CenterLock, 12mm thru-axle
NAPERE	CADEX Aero Carbon Spoke
PLAŠČI	CADEX Road Race GC, tubeless, 700x30mm, folding
DODATKI	computer mount, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	680	710	740	770	800	830
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Višina glave okvirja (mm)	120	130	145	165	185	200
Krmilni kot	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Zamik vpetja osi (mm)	45	45	45	45	45	45
Trail (mm)	72,1	64	59,2	59,2	59,2	59,2
Medosna razdalja (mm)	976	977	980	991	1006	1020
Dolžina cevi ob verigi (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Oddaljenost zgornje cevi od gonilne osi (mm)	517	528	545	562	581	596
Doseg (mm)	376	383	388	393	402	412
Višina zgornje cevi (mm)	719	734	752	768	786	803
Širina krmila (mm)	420	420	440	440	440	440
Dolžina opore krmila (mm)	80	90	100	110	110	120
Dolžina gonilke (mm)	165	165	170	170	172,5	172,5

Vse navedene specifikacije se lahko spremenijo brez obvestila.